

Product information STASEI 3 N grau/grey

Industrial Connecting Solutions: Rectangular Connectors: Power Connectors (ST series): Panel-mounted connector: STASEI 3 N grau/grey

-30 °C to +90 °C

UL 94 HB UL 94 V-0

UL

VDE

SEV

100 pieces

safety brackets STASI 3, order no. 732 045-001

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24351-24356-36011/en/conf/uistate STASEI 3 N grau/grey Name Panel-mounted connector with added gasket **Delivery informations** Availability available **Product description** Panel-mounted connector with added gasket Description STASEI 3 N grau/grey Type Order No. 932 145-106 Type of contact male 3 + PE Number of contacts Conductor size max. 1.5 mm² **Housing Color** grey Contact bearer color black Technical data Pin dimensions 2 mm AC 400 V / DC 250 V Rated voltage Rated current DC 10 A / AC 16 A Contact resistance <= 5 m0hm Type of termination screws Mounting Schrauben Material Contact material Cu Zn Contact surface material Sn PA Contact bearer material Housing material PA **Environmental conditions** Protection class (IEC 60529) IP 54 Pollution severity



Scope of delivery and accessories
Accessories to order separately

Temperature range

Inflammability class
Housing

Contact bearer
Approvals
UL

Packing unit
Packaging unit

VDE

SEV




Industrial Connecting Solutions:Rectangular Connectors:Power Connectors (ST series):Panel-mounted connector:STASEI 3 N grau/grey

http://www.e-catalog.beldensolutions.com/link/57078-24228-256261-24351-24356-36011/en/conf/uistate

Picture

Drawing



Belden Deutschland GmbH

lm Gewerbepark 2 58579 Schalksmühle

Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.

