

NOTES:

- 1. MATERIAL: BRASS QQ-B-626 ALLOY 360 1/2 HARD; ELECTRO-TIN PER ASTM B 545, OVER .0001 NICKEL PLATING, WITH BERYLLIUM COPPER SPRING INSERT CAPTIVATED.
- 2. CONCORD P/N 09-9002-1-04 OR APPROVED EQUIV.
- 3. PARTS SHALL MEET SOLDERABILITY REQUIREMENTS PER MIL-STD-202, METHOD 208 AFTER EXPOSURE TO 8 HRS STEAM AGING PER MIL-STD-883, METHOD 2003.
- 4. RoHS COMPLIANT, LEAD FREE PER CST-0001 LATEST REVISION.

DRAWN BY DATE		
P.E.IENI 05/18/0		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES-		
TOLERANCES ARE: FRACTIONS DECIMALS ANGLE ±1/64 .XX= ±.01 ±1° .XXX=±.005	SOCKET, PIN .040 DIA. PC	
THIRD ANGLE PROJECTION	SIZE FSCM NO. DWG NO	REV
— ———————————————————————————————————	B 67131 30074	4
DO NOT SCALE DRAWING	SCALE SHEET 1 O	F 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vicor: 30074