KEMET Part Number: C2225X102JZGACTU

(C2225X102JZGAC7800)



SMD Comm C0G HV Flex, Ceramic, 1000 pF, 5%, 2500 VDC, C0G, SMD, MLCC, FT-CAP, Ultra-Stable, 2225



Dimensions		
L	5.9mm +/-0.75mm	
W	6.4mm +/-0.4mm	
Т	1.6mm +/-0.20mm	
В	0.7mm +/-0.35mm	

Packaging Specifications		
Packaging:	T&R, 180mm, Plastic Tape	
Packaging Quantity:	1000	

General Information		
Supplier:	KEMET	
Series:	SMD Comm C0G HV Flex	
Style:	SMD Chip	
Description:	SMD, MLCC, FT-CAP, Ultra- Stable	
Features:	FT-CAP, Ultra-Stable	
RoHS:	Yes	
Termination:	Flexible Termination	
Marking:	No	
Chip Size:	2225	

Specifications		
Capacitance:	1000 pF	
Capacitance Tolerance:	5%	
Voltage DC:	2500 VDC	
Dielectric Withstanding Voltage:	3000 VDC	
Temperature Range:	-55/+125C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.10% 1MHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

