

TRACKER II

PROTECTION & FUNCTIONALITY

Ultra-comfortable and technical, Tracker provides protection from all mechanical risks and also chemical risks, making it unique in the safety glasses range.

SUPPLIED WITH : Foam and strap - Microfiber pouch

 52 G

- + VENTED FRAME
- + HIGH IMPACT RESISTANCE (TYPE B: 120M/S)
- + UPPER PROTECTION
- + PLATINUM COATING : ANTI-SCRATCH & ANTI-FOG



TECHNOLOGIES

CSP
PLATINUM

VERSIONS



TRACPSI



TRACPSJ



TRACPSF



TRACWPCC2



TRACWPCC3



TRACWPCC5



 EXCELLENCE
AVAILABLE WITH CORRECTIVE LENSES

TRACKER II

USE	VERSION	REFERENCE	LENS MARKING	FRAME MARKING <small>F: Glasses / B: Glasses with foam and strap kit</small>	COATING	STANDARD
	CLEAR	TRACPSI	2C-1.2 1 BT KN C€	F: EN 166 FT C€ B: EN 166 3 4 BT C€	PLATINUM	EN166-EN170
	AMBER	TRACPSJ	5-1.4 1 BT KN C€	F: EN 166 FT C€ B: EN 166 3 4 BT C€	PLATINUM	EN166-EN172
	SMOKE	TRACPSF	5-2.5 1 BT KN C€	F: EN 166 FT C€ B: EN 166 3 4 BT C€	PLATINUM	EN166-EN172
	WELDING 1.7	TRACWPCC2	1.7 1 FT C€	EN 166 FT C€	ANTI-SCRATCH	EN166-EN169
	WELDING 3	TRACWPCC3	3 1 FT C€	EN 166 FT C€	ANTI-SCRATCH	EN166-EN169
	WELDING 5	TRACWPCC5	5 1 FT C€	EN 166 FT C€	ANTI-SCRATCH	EN166-EN169

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO C€ STANDARDS WILL BE SENT ON REQUEST.



GENERAL SPECIFICATIONS

LENS	POLYCARBONATE - 2.2 MM	FOAM	EVA
CURVE	8 - VERY CURVED	STRAP	NYLON POLYESTER - 200MM
FRAME	POLYCARBONATE - HYBRID	OPTIONAL	



PACKAGING & EAN13 CODE

SINGLE: <small>Size: 27 x 11 x 9 mm</small>	INNER BOX: <small>Size: 24x18x9 cm Weight: 0.91 kg</small>	OUTER PACK: <small>Size: 60 x 50 x 37 cm Weight: 23 kg</small>
3660740004828	3660740104825 -10 pcs	3660740204822 -200 pcs
3660740004842	3660740104849 -10 pcs	3660740204846 -200 pcs
3660740004835	3660740104832 -10 pcs	3660740204839 -200 pcs
3660740000400	3660740100407 -10 pcs	3660740200404 -200 pcs
3660740000417	3660740100414 -10 pcs	3660740200411 -200 pcs
3660740000424	3660740100421 -10 pcs	3660740200428 -200 pcs
CUSTOM CODE: 9004909000		

CLEANING & STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.



MADE IN: CN

DATASHEET: 03-29-2022

bolle-safety.com

Europe Headquarters
34 rue de la Soie
69100 Villeurbanne
France
P : 00 33 (0) 4 78 85 23 64

U.K. & Ireland
Unit C83, Barwell Business Park
Leatherhead Road - Chessington
Surrey - KT9 2NY - UK
P : 00 44 (0)208 391 4700

USA Office
2810 Caribou Court, Suite 160
Carlsbad, CA 92010
United States of America
P : 800 222 6553

Asia-Pacific Office
32-40 Fairchild Street
Heatherton VIC 3202
Australia
P : 1300 138 098



THE PPE EYEWEAR SPECIALISTS