

Products



About TE

What can we help you find?



Support Center My Account Innovation

Home > Products > Modular Jacks & Plugs > Product Feature Selector > Product Details


Resources

5558872-1 Product Details

Industries







5558872-1

PCB Mounted Jacks - Single Port, Multi-port and Stacked

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Preloaded
- Single Port Configuration
- 1 x 1 Jack Configuration
- Jack Type = RJ22

View all Features

Quick Links -

📴 Share

Pricing & Availability

Product Feature Selector

- Search for Tooling
- Contact Us About This Product

TE Internal Number: 5558872-1













Documentation & Additional Information

Product Drawings:

MODULAR JACK ASSEMBLY, TOP ENTRY, 4 POSITION, WITHOU... (PDF, English)

Catalog Pages/Data Sheets:

1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT (PDF, English)

Product Specifications:

Modular Plugs, Thru-Hole and Surface Mount Jacks, Da... (PDF, English)

Application Specifications:

Modular Jacks (PDF, English)

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version B)
- 3D Model (IGES, Version B)
- 3D Model (STEP, Version B)

Additional Information:

Product Line Information

Additional Product Images:

- PCB Layout
- Panel Cutout

Related Products:

Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Jack Type = RJ22
- PCB Mounting Orientation = Top Entry (Vertical)
- PCB Mount Style = Through Hole
- Termination Method to PC Board = Solder
- Performance Category = Cat 3 • LED = Without
- Grounding Options = Without
- Panel Stops = Without
- Keyed = No
- Profile = Standard
- Color = Black
- Latch Style = Standard

Mechanical Attachment:

- Panel Mount Retention = With
- Flanged = No.

Electrical Characteristics:

Shielded = No

Termination Features:

Solder Tail Contact Plating = Tin over Nickel

Dimensions:

- Height (mm [in]) = 16.50 [0.650]
- PCB Tail Length (mm [in]) = 3.18 [0.125]
- PCB Thickness, Recommended (mm [in]) = 1.57 [0.062]

Body Features:

Inverted Jack Face = No

Contact Features:

- Contact Plating, Mating Area, Material = Gold (50)
- Contact Base Material = Phosphor Bronze

Housing Features:

- Housing Material = PBT GF
- UL Flammability Rating = UL 94V-0

Configuration Features:

- Preloaded = Yes
- · Port Configuration = Single
- Jack Configuration = 1 x 1
- Number of Positions = 4
- Number of Contacts Loaded = 4

Industry Standards:

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Packaging Features:

Packaging Method = Tray

Product Availability:

Region = Asia, North America

Other:

Brand = AMP

Corporate Information

About TE Investors News Room Supplier Portal

Terms & Conditions

Careers

Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings

Product Compliance Support Center Site Map

Customer Support Email or Chat With Us Find a Phone Number Knowledge Base Manage Your Account Keep Me Informed



Privacy Policy

Provide Website Feedback