


“low profile“ Sockets & Strips


**Low profile DIP sockets LOP Series**

height above PCB 2.41mm / .095"







**Low profile strips SLP Series**

height above PCB 2.41mm / .095"



**Insulator**



Pin	Dimensions mm/inch		Ordering Code
	"A"	"B"	
14	17,78/.700	7,62 .300	<b>LOP - 314 - S083 - 95</b>
16	20,32/.800		<b>LOP - 316 - S083 - 95</b>
18	22,86/.900		<b>LOP - 318 - S083 - 95</b>
20	25,40/1.000		<b>LOP - 320 - S083 - 95</b>
24	30,48/1.200		<b>LOP - 324 - S083 - 95</b>
		15,24 .600	
24	30,48/1.200		<b>LOP - 624 - S083 - 95</b>
28	35,56/1.400		<b>LOP - 628 - S083 - 95</b>
		15,24 .600	
32	40,64/1.600		<b>LOP - 632 - S083 - 95</b>
40	50,80/2.000		<b>LOP - 640 - S083 - 95</b>
10	25,40/1.000		<b>SLP - 110 - S083 - 95</b>
14	35,56/1.400		<b>SLP - 114 - S083 - 95</b>

**Other sizes and flush head version on request**

**Pin-outs**


*Other pin-outs available on request.*

Despite the very low profile of these sockets the IC legs can be inserted completely.

**Recommended PCB Layout**

*Recommended drilling hole dia Ø 0,8mm/.031"*

**Low Profile Terminal**



**083** 2.41mm / .095" over PCB

**Plating**

**Standard:**

- **95** = tin/gold  
*(tin leadfree)*

**Alternative**

- **55** = gold/gold  
- **99** = tin/ tin  
*(leadfree)*

**Specifications**

**Mechanical data**

Insertion force 1,80 N (avg)  
Extraction force 0,90 N (avg)  
Contact life > 100 cycles  
Solderability as per IEC 60068-2-58  
Contact security:  
-Vibration as per EN60352-4  
-Shock as per EN60352-4

**Material**

Insulator *(RoHS compliant)* PBT UL 94 V-0  
Terminal *(RoHS compliant)* CuZn  
Contact *(RoHS compliant)* BeCu

**Electrical data**

Contact resistance at 1A 4,3 mΩ typ.  
Current rating 1A max., 100V  
Contact capacitance at 1MHz 2 pF max.  
Insulation resistance at 500V DC 5 × 10<sup>9</sup> Ω min.  
Breakdown voltage at 60 Hz 500 V AC  
Contact resistance ≤ 7 mΩ

**Operating temperature**

-55° C to +125° C

**Pitch**

2,54 mm (.100")

**More information, for example about testresult please ref. to page 49 or contact E-tec.**