

Note: This datasheet may be out of date.
Please download the latest datasheet of BLE32PN300SZ1# from the official website of Murata Manufacturing

Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=BLE32PN300SZ1%23

BLE32PN300SZ1#

"#" indicates a package specification code.










< List of part numbers with package codes >

BLE32PN300SZ1L BLE32PN300SZ1K BLE32PN300SZ1B



Appearance & Shape







Features

- 1.Bead inductor BLE series is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.
- 2.The nickel barrier structure of the external electrodes provides excellent solder heat resistance.
- 3.BLE32PN series can be used in high current circuits due to its low DC resistance. It can match power lines to a maximum of 10ADC.

Applications

ı	Automotive
	Usage
ı	Usage

Infotainment



Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	1000
K	330mm Embossed Tape	7000
L	180mm Embossed Tape	1500

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date Please download the latest datasheet of BLE32PN300SZ1# from the official website of Murata Manufacturing

Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=BLE32PN300SZ1%23

BLE32PN300SZ1#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	3225
Size Code (in inch)	1210
Length	3.2mm
Length Tolerance	±0.2mm
Width	2.5mm
Width Tolerance	±0.2mm
Thickness	2.0mm
Thickness Tolerance	±0.2mm
Rated Current	10.0A
Operating Temperature Range	-55°C to 125°C
Mass(typ.)	0.08g
Number of Circuit	1
DC Resistance(max.)	1.6mΩ
Impedance (at 100MHz)	30Ω
Impedance (at 100MHz) Tolerance	±10Ω

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




URL: http://www.murata.com/


Co., Ltd. http://www.murata.com/en-us/products/productdetail?partno=BLE32PN300SZ1%23

BLE32PN300SZ1#

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/