

Product Search Data Sheet

Note: This datasheet may be out of date

Please download the latest datasheet of BLM15BB750SN1# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-us/products/productdetail?partno=BLM15BB750SN1%23

BLM15BB750SN1#

"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > BLM15BB750SN1J BLM15BB750SN1B BLM15BB750SN1D





The chip ferrite beads BLM series is designed to work nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted. BLM series is effective in circuits without stable ground lines because BLM series does not need a connection to ground.

BLM_B series can minimize attenuation of the signal waveform due to its sharp impedance characteristics. Various impedances are available to match signal frequency.

The nickel barrier structure of the external electrodes provides excellent solder heat resistance.

Applications

Other Usage For general

Packaging Information

Packaging	Specifications	Minimum Order Quantity
J	330mm Paper Tape	50000
В	Bulk(Bag)	1000
D	180mm Paper Tape	10000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date

Please download the latest datasheet of BLM15BB750SN1# from the official website of Murata Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=BLM15BB750SN1%23

BLM15BB750SN1#

"#" indicates a package specification code.



SMD Shape 1005 Size Code (in mm) Size Code (in inch) 0402 Length 1.0mm Length Tolerance ±0.05mm Width 0.5mm Width Tolerance ±0.05mm Thickness 0.5mm Thickness Tolerance ±0.05mm Impedance (at 100MHz) 75Ω Impedance (at 100MHz) Tolerance ±25% Rated Current (at 85°C) 300mA Rated Current (at 125°C) 300mA DC Resistance(max.) 0.4Ω **Operating Temperature Range** -55°C to 125°C Mass(typ.) 0.001g Number of Circuit 1

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Product Search Data Sheet

Note: This datasheet may be out of date


Please download the latest datasheet of BLM15BB750SN1# from the official website of Murata Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=BLM15BB750SN1%23


BLM15BB750SN1#

"#" indicates a package specification code.









Impedance-Frequency Characteristics

Equivalent Circuit

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

3 of 3