



Part Number : [1203410300](#)


Product Description : Micro-Change (M12)
CAT6A Double-Ended Cordset, 8 Poles, Male
(Straight) to Male (Straight), 26 AWG, Green
Shielded PUR Cable, 0.50m (1.64') Length

Series Number : 120341

Status : Active

Product Category : Circular Industrial
Cordsets

Engineering Number : E22E06020M005



Documents & Resources

Drawings

[Drawing 1203410300_sd.pdf](#)


[Packaging Design Drawing PK-120341-300-001.pdf](#)

Specifications

[Product Specification PS-120341-001-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2022)4187-DC (10 June 2022)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

ZZCERT_UKCA - Declaration of Conformity : CER_4000410299_00_000.pdf

ZZCERT_CE - Declaration of Conformity : CER_4000410038_00_000.pdf

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120341
Description	Micro-Change (M12) CAT6A Double-Ended Cordset, 8 Poles, Male (Straight) to Male (Straight), 26 AWG, Green Shielded PUR Cable, 0.50m (1.64') Length
IP Rating	IP67
Performance Category	6A
Product Family	Brad Industrial Ethernet Solutions
Product Name	Micro-Change (M12) Cat6A, Industrial Ethernet
Protocol	EtherNet
Region	America, Asia, Europe
Type	Double Ended
UPC	884982411852

Agency

UL	E361772
----	---------

Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	48V

Physical

Cable Diameter	6.90mm (.272")
----------------	----------------

Cable Length	0.50m (1.64')
Color - Cable Jacket	Green
Connector End A	Micro-Change (M12)
Connector End B	Micro-Change (M12)
Coupling Style	Threaded
Gender	Male-Male
Keyway	X-coded
LED Indicator	No
Material - Cable Jacket	PUR
Material - Connector Body	PUR
Material - Contact	Brass
Material - Coupling Nut	Nickel-plated Brass
Material - Plating Mating	Gold
Net Weight	63.600/g
Orientation	Straight to Straight
Poles	8
Temperature Range - Operating	-20° to +80°C
Wire/Cable Type	Shielded PUR
Wire Size (AWG)	26

This document was generated on Sep 05, 2023