


DATA SHEET O-Ring 104408

PART INFORMATION

Part number	104408
Inside diameter d1	4,47 mm
Cross-section d2	1,78 mm
Size standard	BS008/AS008
Tolerance range according to	ISO 3601-1
Rubber family	EPDM
Rubber compound	EP851
Quality acceptance criteria on aspect	ISO 3601-3



EP851 COMPOUND INFORMATION

Original characteristics

Hardness Sh A Tensile strength Elongation at break Compression set TR10 Brittle point Operational temperature range * Peak temperature

Rubber color

16 MPa 160 % 12 % (24h 150°C) -46 °C -55 °C -50 °C / 140 °C 175 °C

Black

80

EPDM FAMILY

Very good resistance

Water, steam and water-based solutions Synthetic brake fluids Atmospheric agents Low temperature

Poor resistance

Mineral oils and hydrocarbons

Particularities

Fairly good mechanical behaviour

Typical applications

Hot and cold water taps Drinking water SF6 circuit breakers Cooling circuit Brake circuit Heating circuit

* The temperature range is given as an indication and can be influenced by the environment, the fluids in contact and the operating conditions.



LE JOINT FRANCAIS SNC 1 rue Gutenberg ZI Ouest de Bazouges - 53200 CHATEAU-GONTIER - FRANCE www.oring.hutchinson.fr - oring@hutchinson.com We make it **possible**