Note: This datasheet may be out of date

Please download the latest datasheet of NFZ2MSD200SN10# from the official website of Murata Manufacturing

Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=NFZ2MSD200SN10%23

NFZ2MSD200SN10#

"#" indicates a package specification code.








< List of part numbers with package codes > NFZ2MSD200SN10L



Appearance & Shape





- 1. NFZ2MSD_SN is a noise filter designed for noise suppression of audio lines such as PC and AV equipment.
- 2. Can be used in high current circuits due to its low DC resistance.
- 3. Low magnetic flux leakage with magnetically shielded structure.
- 4. Meets 125°C maximum operating temperature.



Other Usage

For general



Packaging Information

Packaging	Specifications	Minimum Order Quantity
L	180mm Embossed Tape	3000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/11/21



Note: This datasheet may be out of date

 $\underline{ \text{Please download the latest datasheet of NFZ2MSD200SN10\# from the official website of Murata Manufacturing} \\$

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NFZ2MSD200SN10%23

NFZ2MSD200SN10#

"#" indicates a package specification code.



Shape	SMD
Size Code (in mm)	2016
Size Code (in inch)	0806
Length	2.0mm
Length Tolerance	±0.2mm
Width	1.6mm
Width Tolerance	±0.2mm
Thickness	1.2mm
Thickness Tolerance	max.
Rated Current	3.9A
Operating Temperature Range	-40°C to 85°C
Mass(typ.)	0.0188g
Number of Circuit	1
DC Resistance(max.)	28mΩ
DC Resistance	28mΩ max.
Impedance (at 10MHz)	20Ω
Impedance (at 10MHz) Tolerance	±30%

Operating Temperature Range (Self-temperature rise is included)	-40°C to 125°C
---	----------------

2 of 3

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2019/11/21


^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

https://www.murata.com/en-us/products/productdetail?partno=NFZ2MSD200SN10%23


NFZ2MSD200SN10#

"#" indicates a package specification code.






Max. current (DC, AC) as function of product temperature (derating curve).



Impedance-Frequency Characteristics



Derating of Rated Current

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

