

---

Item no.: 2006-1204  
Product description: 2-Conductor through terminal block suitable for Ex e applications suitable for Ex i applications

---



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Current intensity EN	57 A
Product group	22 (TOPJOB S RAIL-MOUNTED TERMINAL BLOCKS)
Cross section [mm <sup>2</sup> ]	0.5 - 6 mm <sup>2</sup>
Cross section [AWG]	20 - 8 AWG
Connection method	CAGE CLAMP®S Connection
Cross section [mm <sup>2</sup> ]	0.5 - 10 mm <sup>2</sup>
Cross section [AWG]	20 - 8 AWG
Wiring method	s + f-st
Connection method	CAGE CLAMP®S Connection
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	41 A
Rated voltage EN (Ex e II)	550 V
Nominal current (Ex e II)	38 A
Weight	8.975 g
Color	blue
Wiring type	Front-entry

No. of connection Points	2
No. of potentials	1
Height	33 mm
Height	1.299 in



Width	7.5 mm
Width	0.295 in
Depth	57.5 mm
Depth	2.264 in
Strip length from	13 mm
Strip length to	15 mm
Strip length	0.55 in
Customs Tariff No.	85369010
Country of Origin	Deutschland
Mounting	TS 35



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
2006-1204	ABS	05-HG476175/3-PDA	800	41	0,5-16
2006-1204	CCA	NL6342	800	41/57	0,5-6/10
2006-1204	CSA	154112-1543858	600	50	20-8
2006-1204	DNV	E-10423	800	41	0,5-10
2006-1204	GL	26187-05HH	800	41	0,5-6
2006-1204	KEMA	NL2115558.02	800	41	0,5-6
2006-1204	LR	91/20112(E6)	800	41	0,5-10
2006-1204	PRS	TE/1718/880590/08	800	41	0,5-10
2006-1204	PTB	IECEXPTB05.0014U	550	33	0,5-10
2006-1204	PTB	PTB03AteX1030U	550	33	0,5-10
2006-1204	UR	E45172	600	50	20-8

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected