initiastructure for a connected wor

PANDUIT SOLUTIO

Search within category



DESIGN / INSTALL

		UNITED STATES	[CHANGE] ENGLISH	REGISTER / LOG IN	FOLLOWUS
s	PRODUCTS AND SERVICES	SUPPORT ABOUT U	S	Search Panduit	t.com GO
	LOCKOUT CENTER	PSL-1009 Lockout Tagout, 6, Padloo	k Aluminum Board Kit, ʻ	14" x 14".	
	Specs Packaging Deta	ils Documents		Add to Favorites	Add to BOM
	Application		rds communicate the lo pplies—all in the same	ockout safety message w place.	hile storing
	Color	Black/Yellow			
	Dimensions (In.)	14" x 14"			
	Environment	3 years			
	Legend	LOCKOUT CENT	R		
	Length (In.)	14.00			
	Length (mm)	355.6			
	Material	Aluminum			
	Maximum Operating Tempera (°C)	ure 80			
	Maximum Operating Tempera (°F)	ure 176			
	Minimum Operating Temperat (°C)	ure -28			
	Minimum Operating Temperat (°F)	ure -20			
	Overall Width (In.)	14			
	Overall Width (mm)	355.6			
	Part Features	lockout hasps, Thi lockout tags and t Padlocks (keyed o	ck, molded, clear poly p es, Board has holes for ifferently), 3/4" shackle;	ninum pronged hooks to pocket measures 4-3/4" x [•] wall mounting, Kit includ 10 - Laminated Lockout ng; 1 - Standard Scissor	3-5/8" x 2" to hold des: 6 - Steel Tags; 10 - Plastic
	Thickness (In.)	0.063			
	Thickness (mm)	1.6002			
	UL Listed	No			
	RoHS Compliancy Status	Compliant			
	Min. Order Qty.	1			

UNITED STATES [CHANGE] ENGLISH REGISTER / LOG IN FOLLOW US

LEGAL INFORMATION | PRIVACY POLICY | CONTACT US | SITE MAP | WHERE TO BUY | JOBS | UNSUBSCRIBE