

KERN 572-39



All-rounder, e.g. as precision balance in the laboratory or in harsh industrial applications, ideal for the diverse possibilities of Industry 4.0 applications



Functions

Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C

Power supply

Charging time:	8 h
Input voltage:	100 V - 240 V AC 50 / 60 Hz
Mains adapter:	Mains adapter external
Mains adapter/adapter included:	US UK EURO CH
Operating time (Backlight off):	48 h
Operating time (Backlight on):	24 h
Rechargeable battery:	Rchrg. battery optional (factory)

Services (optional)

DAkkS Certificate:	963-127
--------------------	---------

Category

Brand:	KERN
Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 220 mm
Gross weight:	4,400 kg
Net weight:	2,300 kg
Shipping method:	Parcel service

Construction

Casing material:	Cast aluminium alloys
Dimensions housing (WxDxH):	180 x 310 x 85 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	180 x 310 x 90 mm
Revolving screw feet:	yes
Weighing surface (d):	150

Measuring system

Adjustment options:	External calibration
Eccentric loading at 1/3 [Max]:	50 mg
Linearity:	50 mg
Readability [d]:	10 mg
Recommended adjusting weight:	4 kg (E2)
Repeatability:	20 mg
Resolution:	420000
Stabilisation time under laboratory conditions:	3 s
Warm up time:	4 h
Weighing capacity [Max]:	4,200 kg
Weighing system:	Strain gauge
Weighing units:	ffa ct oz ozt tl (HK) kg g mo lb tl (Singap. Malays) dwt tl (Tw)

Display

Display digit height (large):	2,100 cm
-------------------------------	----------

Counting

Counting resolution:	420000
Minimum piece weight at piece counting (Laboratory):	10 mg
Minimum piece weight at piece counting (Normal):	100 mg
Reference weight:	yes

KERN 572-39




All-rounder, e.g. as precision balance in the laboratory or in harsh industrial applications,
ideal for the diverse possibilities of Industry 4.0 applications

Piktogramme

STANDARD



OPTION



FACTORY

