

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 6450
Page 1 of 2 Pages

Issue: 1
Issue Date: 5/20/2008
Effective Date: 5/20/2008

A. Construction

Diameters

- | | | | |
|----|---------------|------------------------|-------|
| 1) | Component 1 | 2 X 1 COAX | |
| | a) Conductor | 18 (7/26) AWG TC | |
| | b) Insulation | 0.025" Wall, Nom. FRPP | 0.096 |
| | (1) Color(s) | | |

Cond	Color	Cond	Color	Cond	Color
1	BLUE	2	WHITE		

- | | | | |
|----|-------------------|--|----------------|
| 2) | Cable Assembly | 2 Components Cabled | |
| | a) Twists: | 6.9 Twists/foot (min) | |
| 3) | Shield: | Alum/Mylar Tape, 25% Overlap, Min. | |
| | a) Foil Direction | Foil Facing Out | |
| | b) Drain Wire | 20 (7/28) AWG TC | |
| | c) Braid | TC, 55% Coverage, Min. | |
| 4) | Jacket | 0.053" Wall, Nom., PVC | 0.324+/- 0.006 |
| | a) Color(s) | BLUE | |
| | b) Print | ALPHA WIRE P/N 6450
EXXXXX 1PR18 SHIELDED (UL) 600V 75C DRY SUN RES
TYPE TC OR PLTC OR ITC OR CMG OR C(UL) CMG ---
P-MSHA (MSHA #) <SEQ FOOTAGE EVERY 2 FT> | |

B. Industry Approvals

- | | | | |
|----|--------------------------------|--|-------------------------------------|
| 1) | UL | TC
PLTC
ITC
CMG
SUN RES | 75°C / 600V
75°C
75°C
75°C |
| 2) | CSA International | CMG
FT4 | 75°C |
| 3) | Other | PMSHA Specification | |
| 4) | EU Directive 2002/95/EC(RoHS): | All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture. | |

C. Physical & Mechanical Properties

- | | | |
|----|-------------------|--------------------|
| 1) | Temperature Range | -40 to 75°C |
| 2) | Bend Radius | 10X Cable Diameter |
| 3) | Pull Tension | 40 Lbs, Maximum |

D. Electrical Properties

- | | | |
|---------------------------------|---------------------------|---|
| (For Engineering purposes only) | | |
| 1) | Voltage Rating | 600 V _{RMS} |
| 2) | Characteristic Impedance | 78 Ω +/- 5 |
| 3) | Inductance | 0.12 μH/ft, Nominal |
| 4) | Mutual Capacitance | 19.5 pf/ft @1 kHz, Nominal |
| 5) | Velocity of Propagation | 65 % |
| 6) | Conductor DCR | 6.9 Ω/1000ft @20°C, Nominal |
| 7) | OA Shield DCR | 3.2 Ω/1000ft @20°C, Nominal |
| 8) | Attenuation, Max dB/100ft | 0.5 @ 1 MHz
2 @ 10 MHz
3.8 @ 50 MHz
5.4 @ 100 MHz
7.6 @ 200 MHz
10.7 @ 400 MHz |

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 6450
Page 2 of 2 Pages

Issue: 1
Issue Date: 5/20/2008
Effective Date: 5/20/2008

E. Other

- 1) Packaging
 - a) 1000 FT
 - b) 500 FT
 - c) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.