

Marker for terminal blocks - UCT1U-TM 5



0803204

<https://www.phoenixcontact.com/in/products/0803204>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

UniCard materials for thermal transfer printers, for marking terminal blocks from Weidmüller, Conta Clip, and Klemsan, 72-section, offset foot, can be marked with THERMOMARK CARD and BLUEMARK, color: white



Marker for terminal blocks - UCT1U-TM 5



0803204

<https://www.phoenixcontact.com/in/products/0803204>

Commercial Data

Order Key	0803204
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	BG2
Catalog Page	Page 162 (C-3-2019)
GTIN	4055626010991
Weight per Piece (including packing)	14.8 GRM
Weight per Piece (excluding packing)	13.0 GRM
Customs tariff number	39269097
Country of origin	PL

Marker for terminal blocks - UCT1U-TM 5



0803204

<https://www.phoenixcontact.com/in/products/0803204>

Technical Data

Notes

General	Can be labeled via thermal transfer
---------	-------------------------------------

Product properties

Type	high
------	------

Marking

Number of individual labels	72
Number of individual labels per row	12

Dimensions

Width	5 mm
Length	10 mm
Pitch	5.2 mm

Material specifications

Color	white
RoHS compliant	Yes
Material	PC
Flammability rating according to UL 94	V0
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Components	free from silicone, halogen, and cadmium

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Specification	VW PV 3.10.7:2005-02
Result	Test passed

Weathering-resistance

Specification	Following ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
Result	Test passed

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Marker for terminal blocks - UCT1U-TM 5



0803204

<https://www.phoenixcontact.com/in/products/0803204>

Test duration	96 h
---------------	------

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	clip on
---------------	---------

Marker for terminal blocks - UCT1U-TM 5



0803204

<https://www.phoenixcontact.com/in/products/0803204>

Classifications

ECLASS

ECLASS-9.0	27141137
ECLASS-10.0.1	27141137
ECLASS-11.0	27281101

ETIM

ETIM 6.0	EC000761
----------	----------

UNSPSC

UNSPSC 19.0	39131505
UNSPSC 20.0	39131505
UNSPSC 21.0	39131505

Marker for terminal blocks - UCT1U-TM 5



0803204

<https://www.phoenixcontact.com/in/products/0803204>

Accessories

Magazine

Magazine - TMP-UCT-MAG1 - 0803342

Magazine, for the THERMOMARK PRIME and the THERMOMARK CARD, for accommodating UCT-TM..., UCT1(U)-TM..., UCT5-TM..., UCT-EM (5x10), UCT-EM (6x10)



Phoenix Contact 2021 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in