

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of 1239AS-H-2R2M# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=1239AS-H-2R2M%23


"#" indicates a package specification code.

In Production General RoHS REACH 85 Wound (Metal)

1239AS-H-2R2M=P2

< List of part numbers with package codes > 1239AS-H-2R2M=P2







Packaging	Specifications	Standard
		Packing
		Quantity
=P2	180Embossed Tape	3000

Mass (typ.)		
1 piece	0.0285g	

(in mm)

1.2 max.



Rated current (Isat) is specified when the decrease of the initial inductance value at 30%. Rated current (Itemp) is specified when temperature of the inductor is raised 40°C by DC current.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Rata Product Search Data Sheet

1239AS-H-2R2M=P2

Note: This datasheet may be out of date. Please download the latest datasheet of 1239AS-H-2R2M# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=1239AS-H-2R2M%23

"#" indicates a package specification code.



Specifications

L size	2.5±0.2mm
W size	2.0±0.2mm
T size	1.2mm
Size code inch (mm)	1008 (2520)
Inductance	2.2µH±20%
Inductance Test Frequency	1MHz
Rated current (Isat) (Based on Inductance change)	2200mA
Rated current (Itemp) (Based on Temperature rise)	2000mA
Max. of DC resistance	0.108Ω
Operating Temperature Range (Self-temperature rise is included)	-40℃ to 85℃
Class of magnetic shield	Metal Alloy
Absolute maximum voltage	20Vdc
Series	DFE252012C

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

1239AS-H-2R2M=P2


Note: This datasheet may be out of date. Please download the latest datasheet of 1239AS-H-2R2M# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-sg/products/productdetail?partno=1239AS-H-2R2M%23

"#" indicates a package specification code.



Characteristic Data





Impedance - Current Characteristics

Temperature Increase Characteristic

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3