

	1	2	3	4	5	6	7																																																																													
A	<p>② SPECIFICATION: Electrical 1. Current rating: 0.5A max. 2. Voltage rating: 90V 3. Insulation resistance: 1000MΩ min. 500VDC 4. Dielectric strength: 500VAC/minute ⑥ 5. Conductor resistance: ≤2.2Ω/m 6. Contact resistance: <20mΩ Mechanical 1. Elongation of insulator: >60% 2. Tensile strength of insulator: >3.5kg/mm² 3. Flexing test: 180° > 20 times 4. Abrasion: >10000 times 5. Durability: >20 cycles Environmental 1. Operating temperature: -40 ~ +105°C 2. Heat resistance: 85°C 96hours 3. Moisture resistance: 40°C 95% RH 96hours 4. Flammability rating: UL Sub. 758 UL20890 105°C 90V VW-1 ④ WSW UL No.: E506903 ⑤ ③ Packaging: 100pcs/PE bag</p>																																																																																			
B	<p>No marking</p>																																																																																			
C	<p>No marking</p>																																																																																			
D	<p>No marking</p>																																																																																			
E	<table border="1"> <thead> <tr> <th colspan="2">Spec</th> <th colspan="2">Spec</th> </tr> </thead> <tbody> <tr> <td>Conductor poles</td> <td>N</td> <td>① 4-80P</td> <td></td> </tr> <tr> <td>Pitch</td> <td>P</td> <td>0.5</td> <td>±0.05</td> </tr> <tr> <td>Total cable length</td> <td>TL</td> <td>see order code</td> <td>Support tape length</td> </tr> <tr> <td>Total pitch</td> <td>PT</td> <td>(N-1)XP</td> <td>B1</td> </tr> <tr> <td>Total width</td> <td>W</td> <td>(N+1)XP</td> <td>B2</td> </tr> <tr> <td>Edge distance</td> <td>M</td> <td>0.5</td> <td>T</td> </tr> <tr> <td></td> <td></td> <td>③ ±0.10</td> <td>T1</td> </tr> <tr> <td></td> <td></td> <td></td> <td>0.303</td> </tr> <tr> <td></td> <td></td> <td></td> <td>0.121</td> </tr> <tr> <td></td> <td></td> <td></td> <td>±0.05</td> </tr> <tr> <td></td> <td></td> <td></td> <td>≤0.3</td> </tr> </tbody> </table> <p>WSW order code: AFFC-050-xx-xxx-11</p> <p>① 04~80 No. of poles</p> <p>Total Cable length 051: 50.80±1mm 076: 76.20±2mm 102: 101.6±2mm 127: 127±2mm 153: 152.4±2mm</p> <table border="1"> <thead> <tr> <th colspan="2">Construction</th> <th colspan="2">Spec.</th> </tr> </thead> <tbody> <tr> <td>①</td> <td>Insulation thickness</td> <td>No marking</td> <td>43µm PET</td> </tr> <tr> <td>②</td> <td>Insulation thickness</td> <td>No marking</td> <td>43µm PET</td> </tr> <tr> <td>③</td> <td>Support tape th. k.</td> <td></td> <td>PET Blue 225µm</td> </tr> <tr> <td>④</td> <td>Conductor (Tinned copper)</td> <td></td> <td>thickness Cl 0.035±0.005</td> </tr> <tr> <td>④</td> <td>Conductor (Tin plated)</td> <td></td> <td>Width CW</td> </tr> <tr> <td></td> <td></td> <td></td> <td>0.30±0.03</td> </tr> </tbody> </table>							Spec		Spec		Conductor poles	N	① 4-80P		Pitch	P	0.5	±0.05	Total cable length	TL	see order code	Support tape length	Total pitch	PT	(N-1)XP	B1	Total width	W	(N+1)XP	B2	Edge distance	M	0.5	T			③ ±0.10	T1				0.303				0.121				±0.05				≤0.3	Construction		Spec.		①	Insulation thickness	No marking	43µm PET	②	Insulation thickness	No marking	43µm PET	③	Support tape th. k.		PET Blue 225µm	④	Conductor (Tinned copper)		thickness Cl 0.035±0.005	④	Conductor (Tin plated)		Width CW				0.30±0.03	
Spec		Spec																																																																																		
Conductor poles	N	① 4-80P																																																																																		
Pitch	P	0.5	±0.05																																																																																	
Total cable length	TL	see order code	Support tape length																																																																																	
Total pitch	PT	(N-1)XP	B1																																																																																	
Total width	W	(N+1)XP	B2																																																																																	
Edge distance	M	0.5	T																																																																																	
		③ ±0.10	T1																																																																																	
			0.303																																																																																	
			0.121																																																																																	
			±0.05																																																																																	
			≤0.3																																																																																	
Construction		Spec.																																																																																		
①	Insulation thickness	No marking	43µm PET																																																																																	
②	Insulation thickness	No marking	43µm PET																																																																																	
③	Support tape th. k.		PET Blue 225µm																																																																																	
④	Conductor (Tinned copper)		thickness Cl 0.035±0.005																																																																																	
④	Conductor (Tin plated)		Width CW																																																																																	
			0.30±0.03																																																																																	
F	<table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th>⑥ Update the conductor resistance description</th> <th>Segal</th> <th>Date</th> <th>Name</th> <th>Description:</th> </tr> </thead> <tbody> <tr> <td>TOLERANCE</td> <td>±5</td> <td>⑤ Update the packing quantity</td> <td>Segal</td> <td>11.12.2019</td> <td>Amy</td> <td>0.5mm pitch FFC cable</td> </tr> <tr> <td>X</td> <td>±1</td> <td>④ Add WSW UL No.</td> <td>Amy</td> <td>14.05.2019</td> <td>Amy</td> <td>ASSMANN WSW-No.</td> </tr> <tr> <td>X.X</td> <td>±0.2</td> <td>③ Add package qty and revise tolerance</td> <td>Amy</td> <td>23.10.2018</td> <td>Amy</td> <td>AFFC-050-XX-XXX-11</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td>② Add specification</td> <td></td> <td></td> <td></td> <td>Drawing-No.</td> </tr> <tr> <td></td> <td></td> <td>① Update the conductor poles</td> <td>Amy</td> <td>22.09.2016</td> <td>Amy</td> <td>ASS 7540 CA</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td>Customer-No.</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>rev06</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>Sheet 1/1</td> </tr> </tbody> </table>							Scale	Free	⑥ Update the conductor resistance description	Segal	Date	Name	Description:	TOLERANCE	±5	⑤ Update the packing quantity	Segal	11.12.2019	Amy	0.5mm pitch FFC cable	X	±1	④ Add WSW UL No.	Amy	14.05.2019	Amy	ASSMANN WSW-No.	X.X	±0.2	③ Add package qty and revise tolerance	Amy	23.10.2018	Amy	AFFC-050-XX-XXX-11	DIM	TOL	② Add specification				Drawing-No.			① Update the conductor poles	Amy	22.09.2016	Amy	ASS 7540 CA	Angle	TOL	Id.	Modification	Date	Name	Customer-No.							rev06							Sheet 1/1														
Scale	Free	⑥ Update the conductor resistance description	Segal	Date	Name	Description:																																																																														
TOLERANCE	±5	⑤ Update the packing quantity	Segal	11.12.2019	Amy	0.5mm pitch FFC cable																																																																														
X	±1	④ Add WSW UL No.	Amy	14.05.2019	Amy	ASSMANN WSW-No.																																																																														
X.X	±0.2	③ Add package qty and revise tolerance	Amy	23.10.2018	Amy	AFFC-050-XX-XXX-11																																																																														
DIM	TOL	② Add specification				Drawing-No.																																																																														
		① Update the conductor poles	Amy	22.09.2016	Amy	ASS 7540 CA																																																																														
Angle	TOL	Id.	Modification	Date	Name	Customer-No.																																																																														
						rev06																																																																														
						Sheet 1/1																																																																														
G	<p>RoHS compliant Unit: mm</p>																																																																																			
H	1	2	3	4	5	6	7																																																																													