

**NEUTRIK**



# NE8FDV-TOP

Vertical PCB panel mount RJ45 receptacle, combined with sealing kit SE8FD-TOP, max. panel thickness 4 mm, mounting screws included.

The etherCON series is a ruggedized and lockable RJ45 connector system, optimized for pro audio, video and lighting network applications. The chassis connectors are shaped to fit into standardized panels out of the entertainment industry. The D-series offers the most rugged design of the etherCON series and is perfectly suitable for panel mount and the installer market.

ATTENTION: Does not intermate with CAT6 cable connector NE8MC6-MO and NKE6S\* cables.

## Features and Benefits

- TRUE OUTDOOR PROTECTION according to IP65 & UL50E
  - Uses high impact UV-resistant and gasket materials
- 
- Outdoor protection when mated with NE8MX-TOP or sealing cap closed
  - Accommodates NE8MCX\* or any standard RJ45 plug
  - Class D or CAT5e according to ISO/IEC 11801 and TIA/EIA
  - Approved latch lock system
  - Mountable from the front of the panel
  - Ground panel connection
- 

## Technical Information

Product	
<b>Title</b>	NE8FDV-TOP
<b>Gender</b>	female
Electrical	
<b>Contact resistance</b>	< 10 mΩ
<b>Dielectric strength</b>	1 kVdc

<b>Frequency range</b>	1 - 100 MHz
<b>Insulation resistance</b>	> 0.5 GΩ
<b>Rated current per contact</b>	1.5 A
<b>Rated voltage</b>	< 50 V
<b>Transmission performance</b>	Class D
<b>Standard compliance</b>	TIA/EIA 586B, IEC11801
<b>Mechanical</b>	
<b>Insertion force</b>	≤ 20 N
<b>Withdrawal force</b>	≤ 20 N
<b>Lifetime</b>	> 1000 mating cycles
<b>Panel thickness</b>	2 mm - 4 mm , 0.08" - 0.16"
<b>Wiring</b>	vertical PCB mount
<b>Locking device</b>	Latch lock
<b>Material</b>	
<b>Contact plating</b>	0.2 μm Au over Ni plating
<b>Contacts</b>	Bronze (CuSn8)
<b>Insert</b>	PBTP 15 % GR
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell plating</b>	Chromium
<b>Environmental</b>	
<b>Flammability</b>	UL 94 V-0
<b>Solderability</b>	Complies with IEC 68-2-20
<b>Temperature range</b>	-30°C to +80 °C

**Protection class**

IP65, UL50E (mated or sealing cap closed)

## Accessories



**SCCD-W**