

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	5025840260		<u> </u>
Status:	Active		
Overview: CLIK-Mate Wire-to-Board C		onnectors	
		CB Receptacle, Single Row, Surface Mount, Tin Plating,	
•			
	Positive Lock, with Pick-and	-Place Polyimide Tape, 2 Circuits, Beige	
Documents:			
<u>3D Model (PDF)</u>		Product Specification 5025781000-PS-000 (PDF)	
<u>3D Model</u>		Application Specification AS-502578-001-001 (PDF)	
Drawing (PDF)		Packaging Specification SPK-502584-001-001 (PDF)	
Product Specification 5025780000-PS-000 (PDF)		RoHS Certificate of Compliance (PDF)	Series image - Reference only
	, , , , , , , , , , , , , , , , , , ,		
General			EU ELV
Product Family		PCB Receptacles	Not Relevant
Series		502584	Not Relevant
		<u>502564</u> Signal, Wire-to-Board	EU RoHS China RoHS
Application Overview		0	Compliant
		CLIK-Mate Wire-to-Board Connectors	REACH SVHC
Product Name		CLIK-Mate	Not Contained Per -
UPC		883906292102	
Physical			D(2021)4569-DC (8
		0	July 2021)
Circuits (Loaded)		2	Halogen-Free
Circuits (maximum)		2	<u>Status</u>
Color - Resin		Beige	Not Low-Halogen
Durability (mating cycles max)		30	For more information, please visit Contact US
Glow-Wire Capable		No	
Guide to Mating Part		Yes	China ROHS Green Image
Keying to Mating Part		None	ELV Not Relevant
Lock to Mating Part		Yes	RoHS Phthalates Not Contained
Mated Height		9.70mm	
Material - Metal		Copper Alloy	
Material - Plating Mating		Tin	Search Parts in this Series
Net Weight		399.547/mg	502584 Series
Number of Rows		1	<u>502504</u> Selles
Orientation		Vertical	
PCB Locator		No	Mates With
PCB Retention		Yes	CLIK-Mate Housing 502578 . CLIK-Mate
Packaging Type		Embossed Tape on Reel	Cable Assembly <u>15135</u>
Pitch - Mating Interface		1.50mm	
Pitch - Termination Interface		1.50mm	
Polarized to Mating Part		Yes	
Polarized to PCB		Yes	
Stackable		No	
Temperature Range - Operating			
Termination Interface: Style		-40° to +105°C	
remination interfa	ice. Siyle	Surface Mount	
Electrical			
Current - Maximum per Contact		2.0A	
Voltage - Maximum		100V	
Material Info			
Reference - Draw	-		
Application Specification		AS-502578-001-001	
Packaging Specification		SPK-502584-001-001	

Application Specification Packaging Specification Product Specification Sales Drawing AS-502578-001-001 SPK-502584-001-001 5025780000-PS-000, 5025781000-PS-000 5025840000-SD-000

This document was generated on 09/14/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION