

DELPHI Connection Systems Catalog

[Customer Service](#)

[Comparison List \(0\)](#)

[Samples Request](#)

Find by Feature

Browse by Category

Browse by Application

Share

Search

Enter part number or keyword

Search Results (1)

Search

Options


1 Result(s): [All] - 15373402

[Compare](#)

15373402 - GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2

[Compare](#)

GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2






Part # 15373402

[Question about this product?](#)

Attributes

Documents (2)

Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	✔ 15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Part # :	15373402
Description :	GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2
Description :	GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2
Description :	GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2
Description :	✔ GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2
Description :	GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2
Description :	GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2
Description :	GT 150 Series Male Sealed Gold Plating Terminal, Cable Range 0.35 - 0.50 mm2

Series :	150
Series :	150
Series :	150
Series :	 150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Series :	150
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	 Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Gender :	Male
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	 Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed

Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Sealable :	Sealed
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	 CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	 0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0
Weight [g] :	0

Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	 Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Plating :	Gold
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	 1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Minimum Cable Diameter [mm] :	1.20
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	 1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85

Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Maximum Cable Diameter [mm] :	1.85
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	 0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Minimum Cable Core Cross Section [mm2] :	0.35
Maximum Cable Core Cross Section [mm2] :	0.50
Maximum Cable Core Cross Section [mm2] :	0.50
Maximum Cable Core Cross Section [mm2] :	0.50
Maximum Cable Core Cross Section [mm2] :	 0.50

Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Voltage Drop :	Less than 10.0
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	✔ precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
Remarks :	precious metal terminal
RoHs compliant :	<input checked="" type="checkbox"/> Yes
ELV compliant :	<input checked="" type="checkbox"/> Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.

