

FEATURES

- Top performances at minimal or maximal pressure drop
- Compact and robust construction
- Quick traceability with laser-printed code on the body

RS PRO Pilot Valve 2/2NC 1/8 ORIF.1.5 FKM

RS Stock No.: 2312784



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO pilot valve 2/2nc 1/8 orif.1.5 FKM has 40 bar maximum allowable pressure. The body is made up of brass. It is use to control liquid and gaseous media with a clean and compact design. A solenoid valve is an electrically controlled valve that allows the flow of liquid or gaseous fluids through the orifice of the valve. The valve opens or closes when the internal plunger moves when a magnetic field is created.

General Specifications

Maximum Working Pressure	40bar
Application	Pneumatic Automation, Robotics, Handling, Automotive Process, Textile, Packaging, Heavy Duty, Food Process, ATEX Zone

Materials	
Body/Sub-Base	Brass
Softseal Spool	FKM

Electrical Specifications

Function	BSP 1/8
Actuation Type	Solenoid Valve
Kv Value (m3/h)	0,06

Mechanical Specifications

Connection Port Thread	Solenoid
Thread Size	1/8in
Mounting Style	2/2 NC

Similar Products

Parameters	2312797	2312798
Brand	RS PRO	RS PRO
Maximum Working Pressure	25 bar	25 bar
Kv Value (m3/h)	10.97	10.97
Thread Size	1"	1"