Detailed Specifications & Technical Data

METRIC MEASUREMENT VERSION



AX101100 Cable Assemblies - Breakout Kit - 6-Fiber





For more Information please call

1-800-Belden1



General Description:

Breakout Kit, 6-Fiber with 36 inches 900um Buffer Tubes

Usage ((Overall)	

Suitable Applications: Data Centers, Main Equipment Rooms, Telecommunications Rooms Related Parts: Optimax, Loos Tube Fiber Cables

Physical Characteristics (Connectivity)

Weight

0.000 kg Weight:

Packaging

Individually packaged, 100 by box

Mechanical Characteristics (Connectivity)

-40°C To +75°C Storage Temperature Range: Operating Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS): EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2006 FUP 50 MII Order #39 (China RoHS): Safety Listing: ACA Suitability Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: This part comes with a printed label, an alcool pad and instruction sheets. For additional information about this product visit our web site at http://www.belden.com.

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX101100	1 EA	0.090 LB			BREAKOUT KIT - 6 FIBERS

Revision Date: 05-20-2011 Revision Number: 0

© 2016 Belden, Inc All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/5FC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Page 1 of 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Belden Wire & Cable: