

Features

Regulated Converters

- Regulated Output
- 1kVDC, 2kVDC & 3kVDC Isolation Options
- Continuous Short Circuit Protection
- Auto-Restarting
- Wide Input 2:1 & 4:1
- UL94V-0 Package Material
- Cost Effective
- 100% Burned In
- Efficiency to 86%

Selection Guide

Part Number	Input Voltage (VDC)	Output Voltage (VDC)	Max Cap. Load (μF)	Output Current (mA)	Efficiency (%)
REC3-xx3.3SRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	3.3	2200	900	66-76
REC3-xx05SRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	5	1000	600	71-79
REC3-xx09SRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	9	470	330	74-83
REC3-xx12SRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	12	220	250	75-85
REC3-xx15SRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	15	120	200	75-86
REC3-xx05DRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±5	±470	±300	74-83
REC3-xx09DRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±9	±220	±165	81-84
REC3-xx12DRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±12	±100	±125	75-85
REC3-xx15DRW/H*	4.5 - 9, 9 - 18, 18 - 36, 36 - 72	±15	±68	±100	75-86
REC3-xx3.3SRWZ/H*	9 - 36, 18 - 72	3.3	2200	900	77-79
REC3-xx05SRWZ/H*	9 - 36, 18 - 72	5	1000	600	78-80
REC3-xx09SRWZ/H*	9 - 36, 18 - 72	9	470	330	80-83
REC3-xx12SRWZ/H*	9 - 36, 18 - 72	12	220	250	83-85
REC3-xx15SRWZ/H*	9 - 36, 18 - 72	15	120	200	83-85
REC3-xx05DRWZ/H*	9 - 36, 18 - 72	±5	±470	±300	77-80
REC3-xx09DRWZ/H*	9 - 36, 18 - 72	±9	±220	±165	81-84
REC3-xx12DRWZ/H*	9 - 36, 18 - 72	±12	±100	±125	83-85
REC3-xx15DRWZ/H*	9 - 36, 18 - 72	±15	±68	±100	83-85

2:1 Input
(REC3-S/DRW/H*)
xx = 4.5-9Vin = 05
xx = 9-18Vin = 12
xx = 18-36Vin = 24
xx = 36-72Vin = 48

4:1 Input
(REC3-S/DRWZ/H*)
xx = 9-36Vin = 24
xx = 18-72Vin = 48

* use suffix **/H1** for 1kVDC Isolation, **/H2** for 2kVDC Isolation or **/H3** for 3kVDC Isolation.
* add suffix **"A"**, **"B"** or **"C"** for Pinning, see next page
* add suffix **"M"** for metal case
* add suffix **"SMD"** for SMD package
e.g. REC3-2412SRW/H1/A/M = 1kVDC isol.
/ Pinout "A" / metal case

Notes:


If the options **"M"** for metal case and **"SMD"** for SMD pinout are combined the maximum allowed isolation voltage is 2kVDC because of the shorter distances between the pins and the metal-case so the only available SMD-option in metal-case is **"H2"**. DIP-24 through-hole case and SMD-plastic case are not affected and offer the full isolation barriers of 2kVDC for **"H2"** option and 3kVDC for **"H3"**.
The **/H2** and **/H3** Version is not available in **"B"** Pinning.

ECONOLINE

DC/DC-Converter

REC3-S_DRW(Z)/H* Series

3 Watt
DIP24 & SMD
Single & Dual
Output





EN-60950-1 Certified
EN-60601-1 Certified
(Suffix H3)
UL-60950-1 Certified

RECOM

Specifications (Core Operating Area)




Input Voltage Range		2:1 & 4:1
Output Voltage Accuracy		±2% max.
Line Regulation (HL-LL)	2:1 Input types	±0.3% max.
	4:1 Input types	±0.3% max.
Load Regulation (for output load current change from 20% to 100%)		±0.6% max.
Output Ripple and Noise (0,1µF capacitor on output, 20MHz BW)		50mVp-p max.
Switching Frequency at Full Load and nominal Input Voltage	2:1 Input types	90kHz min. / 150kHz max.
	4:1 Input types	120kHz min. / 180kHz max.
Input Filter		Network
Efficiency at Full Load		see above
No Load Power Consumption		300mW max.
Isolation Voltage	H1 types	tested for 1 second)
Rated Working Voltage		(long term isolation)
		1000VDC min.
		see Application Notes
Isolation Voltage	H2 types	(tested for 1 second)
Rated Working Voltage		(long term isolation)
		2000VDC min.
		see Application Notes
Isolation Voltage	H3 types	(tested for 1 second)
Rated Working Voltage		(long term isolation)
		3000VDC min.
		see Application Notes
Isolation Capacitance	2:1 Input types	20pF min. / 60pF max.
	4:1 Input types	40pF min. / 80pF max.
Isolation Resistance		1 GΩ min.
Short Circuit Protection		Continuous, Auto Restart
Operating Temperature Range (free air convection)	5V input types	-40°C to +80°C (see Graph)
	others	-40°C to +85°C (see Graph)
Storage Temperature Range		-55°C to +125°C
Relative Humidity		95% RH
Case Material		Non-Conductive Plastic
Thermal Impedance		Natural convection
		20°C/W for metal case
Package Weight		13g
MTBF (+25°C)	} Detailed Information see Application Notes chapter "MTBF"	using MIL-HDBK 217F
		1043 x 10 ³ hours
MTBF (+85°C)	}	using MIL-HDBK 217F
		186 x 10 ³ hours

Derating-Graph (Ambient Temperature)




Package Style and Pinning (mm) DIP 24 , Wide Input 2:1 & 4:1

Package A



Recommended Footprint Details



Pin Connections

Pin #	Single	Dual
2	-Vin	-Vin
3	-Vin	-Vin
9	NC	Com
11	NC	-Vout
14	+Vout	+Vout
16	-Vout	Com
22	+Vin	+Vin
23	+Vin	+Vin

NC = No Connection



XX.X ± 0.5 mm

XX.XX ± 0.25 mm





Package B

/H1 Only



Recommended Footprint Details





Pin Connections



Pin #	Single	Dual
1	+Vin	+Vin
2	No Pin	-Vout
3	No Pin	Com
10	-Vout	Com
11	+Vout	+Vout
12	-Vin	-Vin
13	-Vin	-Vin
14	+Vout	+Vout
15	-Vout	Com
22	No Pin	Com
23	No Pin	-Vout
24	+Vin	+Vin

NC = No Connection
XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Package C



Recommended Footprint Details





Pin Connections



Pin #	Single	Dual
1	+Vin	+Vin
2	+Vin	+Vin
10	NC	Com
11	NC	Com
12	-Vout	NC
13	+Vout	-Vout
15	NC	+Vout
23	-Vin	-Vin
24	-Vin	-Vin

NC = No Connection
XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Mechanical drawings of DIP24 SMD case



Recommended Footprint Details



All unused pins are
NC (No Connection).
SMD pin connections
follow standard
package pinning. See
Notes for restrictions
on /H3 SMD versions.

Tol.: ± 0.35 mm

length of plastic case is 31,8mm, length of metal case 32.0mm