

This document was generated on 08/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0353620250		A
Status:	Active		
ACTIVE		d Connector System	
Description:	Sherlock Wire-to-Board Connector System 2.00mm Pitch Sherlock Wire-to-Board Header, Vertical, with Positive Lock, 2 Circuits,		
Description.	with Kinked PC Tails		
		s, Natural	
Documents:			The GM
3D Model		Product Specification DS 25507 002 001 (DDE)	
Drawing (PDF)		Product Specification PS-35507-003-001 (PDF) Packaging Specification PK-35362-001-001 (PDF)	¥ VI
<u>3D Model (PDF)</u>		RoHS Certificate of Compliance (PDF)	-4
			- Series image - Reference only
Agonov Cortification			
Agency Certification		LR19980	EU ELV
UL		E29179	Not Relevant
UL		229175	NOT Relevant
General			EU RoHS China RoHS
Product Family		PCB Headers	Compliant
Series		<u>35362</u>	REACH SVHC
Application		Signal, Wire-to-Board	Not Contained Per -
Overview		Sherlock Wire-to-Board Connector System	D(2021)4569-DC (8
Product Name		Sherlock	July 2021)
UPC		822348257720	Halogen-Free
			Status
Physical			Low-Halogen
Breakaway		No	For more information, please visit Contact US
Circuits (Loaded)		2	<u></u>
Circuits (maximum)		2	China ROHS Green Image
Color - Resin		Natural	ELV Not Relevant
Durability (mating cycles max)		30	RoHS Phthalates Not Contained
First Mate / Last Break		No	
Flammability		94V-0	
Glow-Wire Capable		No	Search Parts in this Series
Guide to Mating Part		No	<u>35362</u> Series
Keying to Mating Part		None	
Lock to Mating Part		Yes	Mates With
Mated Height		8.50mm	<u>35507</u> Sherlock Wire-to-Board Housing
Material - Plating Mating		Tin	3007 Shenock Wile-to-Board Housing
Material - Plating Termination Material - Resin		Tin	
Net Weight		Nylon	Use With
Number of Rows		0.206/g	<u>502128000</u> Terminal
Orientation		Vertical	
PC Tail Length		3.30mm	
PCB Locator		No	
PCB Retention		Yes	
PCB Thickness - Recommended		1.60mm	
PCB mickness - Reco Packaging Type		Bag	
Pitch - Mating Interface		2.00mm	
Pitch - Termination Interface		2.00mm	
Polarized to Mating Pa		Yes	
Polarized to PCB		No	
Shrouded		Partial	
Stackable		No	
Surface Mount Compa	tible (SMC)	No	
Temperature Range - (-40° to +105°C	
Termination Interface:		Through Hole	
remmanon mienace.	Otyle	THOUGH HOLE	

Electrical

Current - Maximum per Contact Voltage - Maximum

Material Info

Reference - Drawing Numbers Packaging Specification Product Specification Sales Drawing

PK-35362-001-001 PS-35507-003-001 SD-35362-002-002

2.0A

125V

This document was generated on 08/26/2021 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION