



RECOMMENDED PCB LAYOUT

DIMENSION

A	(N-1)×3.81+5.0
B	(N-1)×3.81

N= number of poles

Poles	Tolerance
2P-6P	±0.15
7P-12P	±0.20
13P-18P	±0.25
19P-24P	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	04/20'06	Added feature	Marvin
△	8/16'06	Added VDE standard	Steady
△	1/12'07	Soldering temperature changed from 245° to 250°	Tony
△	5/27'08	Operating temperature is changed	Marvin
△	2009.08.18	The material is changed	Jacke
△	2010.07.07	Remove the CSA mark	Chen Bo
△	2010.12.21	Dim changed from 2.6 to 2.5	Runner
△	2012.05.22	Voltage rating is changed	Chen Bo
△	2012.06.04	The color is added	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- ⑤ ● Item ⑤ Male contact pin: Copper Tin plated
- Item ⑥ Terminalhousing: Thermoplastic (UL94V-0)

- Electrical: cULus /VDE
- ⑧ ● Voltage rating: 300V/300V
- Current rating: 10A/10.5A
- Withstanding Voltage: 1.6 KV/2.5KV
- ④ ● Operating temperature: -40°C to +115°C
- ③ ● Soldering temperature: 250°C±10°C/5 Sec
- ⑥ ● Safety Approval:
- Critical dimension:

OQ xx 3 2 x 0 xxxx G

No. OF POLES  
02: 2 POLES

24: 24 POLES

Color

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- ⑨ C Green(RAL6018/U)

G RoHS compliant (lead<4%)  
In copper Alloy  
0000: "@ " Logo  
000A: "ANYTEK" Logo  
Any special item by customer request. please contact sales department.

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE				OQ 3.81mm Series 180° (2P-24P) Triangle Key Lock			
PART NO.		OQxx32x0xxxxG		DWG NO.		80Q0601	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Chen Bo	Chen Bo			X.	±0.50
		06/04`12	05/14`12			X.X	±0.30
				SHEET: 01/01		UNIT: mm	X.XX ±0.10
						SCALE: NONE	X° ±1°
						REV.: N	