

Product Search Data Sheet


Note: This datasheet may be out of date Please download the latest datasheet of CSTNE16M0VH3C000R0 from the official website of Murata Manufacturing Co., Ltd. uctdetail?partno=CSTNE16M0VH3C000R0

CSTNE16M0VH3C000R0



Appearance & Shape







MURATA's frequency adjustment and packaging technology expertise has enabled the development of the chip CERALOCK(R) with built-in load capacitors. This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

Features

1. High accuracy resonators whose total tolerance is available for less than +-3,000ppm.

- 2. High reliability and available for a wide temperature range.
- 3. Oscillation circuits do not require external load capacitors.
- 4. Available for a wide frequency range.
- 5. Extremely small and have a low profile.
- 6. No adjustment is necessary for oscillation circuits.
- 7. Stable supply is ensured due to not using precious metal(Palladium).

Applications

Automotive Usage	Powertrain/Safety
Other Usage	Automotive

Packaging Information

Packaging	Specifications	Minimum Order Quantity
R0	180mm Embossed Tape	3000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of CSTNE16M0VH3C000R0 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en/products/productdetail?partno=CSTNE16M0VH3C000R0

CSTNE16M0VH3C000R0

Specifications

Product Type	Ceramic Resonator (CERALOCK®)	
Series	CSTNE_VH3C	
Frequency	16.000MHz	
Frequency Tolerance	+/-0.07% max.	
Operating Temperature Range	-40°C to 125°C	
Frequency Shift by Temperature	+/-0.13% max.	
Frequency Aging	+/-0.07% max.	
Resonant Impedance (R1)	40ohm max.	
Built-in Load Capacitance(CL1/CL2)	15pF	
Shape	SMD	
Wash	available	
L x W (size)	3.2x1.3mm	

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention

2 of 2