

# HUBER+SUHNER® DATA SHEET

## Between Series Adaptor: 33\_SMA-MMBX-50-1/119\_N

Rev.: D



### Description

Adaptor plug/jack  
SMA plug (male) / MMBX jack (female)

Interface standards

Series SMA - IEC 60169-15\_MIL-STD-348A/310\_CECC 22110

Series MMBX - SUHNER-MMBX



### Technical Data

#### Electrical Data

Impedance	50 Ω		
Interface frequency max.	6 GHz		
Frequency range	DC to 2.5 GHz	2.5 to 6 GHz	6 to 12.4 GHz
Return loss	≥ 32 dB	≥ 30 dB	≥ 16 dB

#### Mechanical Data

Number of matings	500
Weight	0.0039 kg

#### Environmental Data

Operating Temperature	-55 °C to 155 °C
2002/95/EC (RoHS)	compliant

#### Material Data

##### Piece Parts

##### Interface - SMA plug (male)

	Material
Centre contact	Copper Beryllium Alloy
Outer contact	Copper Beryllium Alloy
Body	Copper Beryllium Alloy
Insulator	PFA / PTFE
Coupling nut	Stainless Steel

##### Surface Plating

Gold Plating (Nickel underplated)
SUCOPRO Plating
SUCOPRO Plating
Passivated (Plating)

##### Interface - MMBX jack (female)

Centre contact	Copper Beryllium Alloy
Outer contact	Brass
Body	Brass
Insulator	LCP (Liquid crystal polymer)

Gold Plating (Nickel underplated)
SUCOPRO Plating
SUCOPRO Plating

#### Related Documents

Outline drawing	DOU-00013970
-----------------	--------------

#### Ordering Information

Single package	33_SMA-MMBX-50-1/119_NE
----------------	-------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**