

## Features

- Thin small outline package (TSOP-I) configurable as 1 M × 16 or as 2 M × 8 SRAM
- Wide voltage range: 2.2 V–3.6 V
- Ultra-low active power:  
Typical active current: 2 mA at f = 1 MHz
- Ultra-low standby power
- Easy memory expansion with  $\overline{CE}_1$ ,  $CE_2$  and  $\overline{OE}$  features
- Automatic power-down when deselected
- Complementary metal oxide semiconductor (CMOS) for optimum speed / power
- Available in Pb-free and non Pb-free 48-ball very fine-pitch ball grid array (VFBGA) and 48-pin TSOP I package

## Functional Description

The CY62167DV30 is a high-performance CMOS static RAM organized as 1M words by 16-bits. This device features advanced circuit design to provide ultra-low active current. This is ideal for providing More Battery Life™ (MoBL®) in portable applications such as cellular telephones. The device also has an


automatic power-down feature that significantly reduces power consumption by 99% when addresses are not toggling. The device can also be put into standby mode when deselected ( $\overline{CE}_1$  HIGH or  $CE_2$  LOW or both  $\overline{BHE}$  and  $\overline{BLE}$  are HIGH). The input/output pins ( $I/O_0$  through  $I/O_{15}$ ) are placed in a high-impedance state when: deselected ( $\overline{CE}_1$  HIGH or  $CE_2$  LOW), outputs are disabled ( $\overline{OE}$  HIGH), both Byte High Enable and Byte Low Enable are disabled ( $\overline{BHE}$ ,  $\overline{BLE}$  HIGH), or during a Write operation ( $\overline{CE}_1$  LOW,  $CE_2$  HIGH and  $\overline{WE}$  LOW).

Writing to the device is accomplished by taking Chip Enables ( $\overline{CE}_1$  LOW and  $CE_2$  HIGH) and Write Enable ( $\overline{WE}$ ) input LOW. If Byte Low Enable ( $\overline{BLE}$ ) is LOW, then data from I/O pins ( $I/O_0$  through  $I/O_7$ ), is written into the location specified on the address pins ( $A_0$  through  $A_{19}$ ). If Byte High Enable ( $\overline{BHE}$ ) is LOW, then data from I/O pins ( $I/O_8$  through  $I/O_{15}$ ) is written into the location specified on the address pins ( $A_0$  through  $A_{19}$ ).

Reading from the device is accomplished by taking Chip Enables ( $\overline{CE}_1$  LOW and  $CE_2$  HIGH) and Output Enable ( $\overline{OE}$ ) LOW while forcing the Write Enable ( $\overline{WE}$ ) HIGH. If Byte Low Enable ( $\overline{BLE}$ ) is LOW, then data from the memory location specified by the address pins appear on  $I/O_0$  to  $I/O_7$ . If Byte High Enable ( $\overline{BHE}$ ) is LOW, then data from memory appear on  $I/O_8$  to  $I/O_{15}$ . See the truth table at the back of this data sheet for a complete description of Read and Write modes.

For a complete list of related documentation, [click here](#).

## Logic Block Diagram



## Contents

|   |           |  |           |
|---|-----------|--|-----------|
| <b>Product Portfolio</b> .....              | <b>3</b>  | <b>Ordering Information</b> .....                    | <b>13</b> |
| <b>Pin Configurations</b> .....             | <b>3</b>  | Ordering Code Definitions .....                      | 13        |
| <b>Maximum Ratings</b> .....                | <b>4</b>  | <b>Package Diagrams</b> .....                        | <b>14</b> |
| <b>Operating Range</b> .....                | <b>4</b>  | <b>Acronyms</b> .....                                | <b>16</b> |
| <b>Electrical Characteristics</b> .....     | <b>4</b>  | <b>Document Conventions</b> .....                    | <b>16</b> |
| <b>Capacitance</b> .....                    | <b>5</b>  | Units of Measure .....                               | 16        |
| <b>Thermal Resistance</b> .....             | <b>5</b>  | <b>Document History Page</b> .....                   | <b>17</b> |
| <b>AC Test Loads and Waveforms</b> .....    | <b>5</b>  | <b>Sales, Solutions, and Legal Information</b> ..... | <b>18</b> |
| <b>Data Retention Characteristics</b> ..... | <b>6</b>  | Worldwide Sales and Design Support .....             | 18        |
| <b>Data Retention Waveform</b> .....        | <b>6</b>  | Products .....                                       | 18        |
| <b>Switching Characteristics</b> .....      | <b>7</b>  | PSoC® Solutions .....                                | 18        |
| <b>Switching Waveforms</b> .....            | <b>8</b>  | Cypress Developer Community .....                    | 18        |
| <b>Truth Table</b> .....                    | <b>12</b> | Technical Support .....                              | 18        |

## Product Portfolio

| Product       | V <sub>CC</sub> Range (V) |                    |                      | Speed (ns) | Power Dissipation              |     |                    |     |                               |     |
|---------------|---------------------------|--------------------|----------------------|------------|--------------------------------|-----|--------------------|-----|-------------------------------|-----|
|               |                           |                    |                      |            | Operating I <sub>CC</sub> (mA) |     |                    |     | Standby I <sub>SB2</sub> (μA) |     |
|               | f = 1 MHz                 |                    | f = f <sub>Max</sub> |            |                                |     |                    |     |                               |     |
|               | Min                       | Typ <sup>[1]</sup> | Max                  |            | Typ <sup>[1]</sup>             | Max | Typ <sup>[1]</sup> | Max | Typ <sup>[1]</sup>            | Max |
| CY62167DV30LL | 2.2                       | 3.0                | 3.6                  | 55         | 2                              | 4   | 15                 | 30  | 2.5                           | 22  |
|               |                           |                    |                      | 70         |                                |     | 12                 | 25  |                               |     |

## Pin Configurations

Figure 1. 48-ball VFBGA pinout (Top View) [2, 3]





Figure 2. 48-pin TSOP I pinout (Top View) [4]



### Notes

1. Typical values are included for reference only and are not guaranteed or tested. Typical values are measured at V<sub>CC</sub> = V<sub>CC</sub>(typ.), T<sub>A</sub> = 25 °C.
2. NC pins are not connected on the die.
3. DNU pins have to be left floating.
4. The BYTE pin in the 48-TSOP I package has to be tied to V<sub>CC</sub> to use the device as a 1M X 16 SRAM. The 48-TSOP I package can also be used as a 2 M x 8 SRAM by tying the BYTE signal to V<sub>SS</sub>. In the 2 M x 8 configuration, Pin 45 is A20, while BHE, BLE and I/O8 to I/O14 pins are not used (DNU).

## Maximum Ratings

Exceeding maximum ratings may shorten the useful life of the device. User guidelines are not tested.

Storage temperature ..... -65 °C to +150 °C  
 Ambient temperature with power applied ..... -55 °C to +125 °C  
 Supply voltage to ground potential ..... -0.2 V to  $V_{CC} + 0.3$  V  
 DC voltage applied to outputs in High-Z state <sup>[5, 6]</sup> ..... -0.2 V to  $V_{CC} + 0.3$  V  
 DC input voltage <sup>[5, 6]</sup> ..... -0.2 V to  $V_{CC} + 0.3$  V  
 Output current into outputs (LOW) ..... 20 mA

Static discharge voltage (per MIL-STD-883, Method 3015) ..... > 2001 V

Latch-up current ..... > 200 mA

## Operating Range

| Device        | Range      | Ambient Temperature | $V_{CC}$ <sup>[7]</sup> |
|---------------|------------|---------------------|-------------------------|
| CY62167DV30LL | Industrial | -40 °C to +85 °C    | 2.20 V to 3.60 V        |

## Electrical Characteristics

Over the Operating Range

| Parameter | Description                                | Test Conditions   | CY62167DV30-55 |                    |                | CY62167DV30-70 |                    |                | Unit    |
|-----------|--|---|----------------|--------------------|----------------|----------------|--------------------|----------------|---------|
|           |  |   | Min            | Typ <sup>[8]</sup> | Max            | Min            | Typ <sup>[8]</sup> | Max            |         |
| $V_{OH}$  | Output HIGH voltage                        | $I_{OH} = -0.1$ mA, $V_{CC} = 2.20$ V   | 2.0            | –                  | –              | 2.0            | –                  | –              | V       |
|           |  | $I_{OH} = -1.0$ mA, $V_{CC} = 2.70$ V   | 2.4            |                    |                | 2.4            |                    |                |         |
| $V_{OL}$  | Output LOW voltage                         | $I_{OL} = 0.1$ mA, $V_{CC} = 2.20$ V  | –              | –                  | 0.4            | –              | –                  | 0.4            | V       |
|           |  | $I_{OL} = 2.1$ mA, $V_{CC} = 2.70$ V  |                |                    |                |                |                    |                |         |
| $V_{IH}$  | Input HIGH voltage                         | $V_{CC} = 2.2$ V to 2.7 V   | 1.8            | –                  | $V_{CC} + 0.3$ | 1.8            | –                  | $V_{CC} + 0.3$ | V       |
|           |  | $V_{CC} = 2.7$ V to 3.6 V   | 2.2            |                    |                | 2.2            |                    |                |         |
| $V_{IL}$  | Input LOW voltage                          | $V_{CC} = 2.2$ V to 2.7 V   | -0.3           | –                  | 0.6            | -0.3           | –                  | 0.6            | V       |
|           |  | $V_{CC} = 2.7$ V to 3.6 V   |                |                    | 0.8            |                |                    | 0.8            |         |
| $I_{IX}$  | Input leakage current                      | $GND \leq V_I \leq V_{CC}$  | -1             | –                  | +1             | -1             | –                  | +1             | $\mu$ A |
| $I_{OZ}$  | Output leakage current                     | $GND \leq V_O \leq V_{CC}$ , output disabled  | -1             | –                  | +1             | -1             | –                  | +1             | $\mu$ A |
| $I_{CC}$  | $V_{CC}$ operating supply current          | $V_{CC} = V_{CC(max)}$<br>$I_{OUT} = 0$ mA<br>CMOS levels<br>$f = 1$ MHz  | –              | 15                 | 30             | –              | 12                 | 25             | mA      |
|           |  |   |                | 2                  | 4              |                | 2                  | 4              |         |
| $I_{SB1}$ | Automatic power-down current – CMOS inputs | $\overline{CE}_1 \geq V_{CC} - 0.2$ V or $CE_2 \leq 0.2$ V,<br>$V_{IN} \geq V_{CC} - 0.2$ V, $V_{IN} \leq 0.2$ V,<br>$f = f_{Max}$ (address and data only),<br><br>$f = 0$ ( $\overline{OE}$ , $\overline{WE}$ ), $V_{CC} = 3.60$ V | –              | 2.5                | 22             | –              | 2.5                | 22             | $\mu$ A |
| $I_{SB2}$ | Automatic power-down current – CMOS Inputs | $\overline{CE}_1 \geq V_{CC} - 0.2$ V or<br>$CE_2 \leq 0.2$ V<br>$V_{IN} \geq V_{CC} - 0.2$ V or $V_{IN} \leq 0.2$ V,<br>$f = 0$ , $V_{CC} = 3.60$ V  | –              | 2.5                | 22             | –              | 2.5                | 22             | $\mu$ A |

### Notes

- $V_{IL(min)}$  = -2.0 V for pulse durations less than 20 ns.
- $V_{IH(max)}$  =  $V_{CC} + 0.75$  V for pulse durations less than 20 ns.
- Full Device AC operation requires linear  $V_{CC}$  ramp from 0 to  $V_{CC(min)}$  and  $V_{CC}$  must be stable at  $V_{CC(min)}$  for 500  $\mu$ s.
- Typical values are included for reference only and are not guaranteed or tested. Typical values are measured at  $V_{CC} = V_{CC(typ)}$ ,  $T_A = 25$  °C.

### Capacitance


| Parameter <sup>[10]</sup> | Description        | Test Conditions   | Max | Unit |
|---------------------------|--------------------|---|-----|------|
| C <sub>IN</sub>           | Input capacitance  | T <sub>A</sub> = 25 °C, f = 1 MHz, V <sub>CC</sub> = V <sub>CC(typ)</sub> | 8   | pF   |
| C <sub>OUT</sub>          | Output capacitance |   | 10  | pF   |

### Thermal Resistance

| Parameter <sup>[10]</sup> | Description                              | Test Conditions  | VFBGA | TSOP I | Unit |
|---------------------------|--|--|-------|--------|------|
| θ <sub>JA</sub>           | Thermal resistance (junction to ambient) | Still air, soldered on a 3 × 4.5 inch, 2-layer printed circuit board | 55    | 60     | °C/W |
| θ <sub>JC</sub>           | Thermal resistance (junction to case)    |  | 16    | 4.3    | °C/W |

### AC Test Loads and Waveforms

Figure 3. AC Test Loads and Waveforms




| Parameters      | 2.5 V | 3.0 V | Unit |
|-----------------|-------|-------|------|
| R1              | 16667 | 1103  | Ω    |
| R2              | 15385 | 1554  | Ω    |
| R <sub>TH</sub> | 8000  | 645   | Ω    |
| V <sub>TH</sub> | 1.20  | 1.75  | V    |

## Data Retention Characteristics

Over the Operating Range

| Parameter        | Description                          | Conditions   | Min | Typ <sup>[9]</sup> | Max | Unit          |
|------------------|--------------------------------------|--|-----|--------------------|-----|---------------|
| $V_{DR}$         | $V_{CC}$ for data retention          |  | 1.5 | –                  | –   | V             |
| $I_{CCDR}$       | Data retention current               | $V_{CC} = 1.5\text{ V}$ ,<br>$\overline{CE}_1 \geq V_{CC} - 0.2\text{ V}$ or $CE_2 \leq 0.2\text{ V}$ ,<br>$V_{IN} \geq V_{CC} - 0.2\text{ V}$ or $V_{IN} \leq 0.2\text{ V}$ | –   | –                  | 10  | $\mu\text{A}$ |
| $t_{CDR}^{[10]}$ | Chip deselect to data retention time |  | 0   | –                  | –   | ns            |
| $t_R^{[11]}$     | Operation recovery time              | CY62167DV30LL-55   | 55  | –                  | –   | ns            |
|                  |                                      | CY62167DV30LL-70   | 70  |                    |     |               |

## Data Retention Waveform



### Notes

9. Typical values are included for reference only and are not guaranteed or tested. Typical values are measured at  $V_{CC} = V_{CC(\text{typ})}$ ,  $T_A = 25\text{ }^\circ\text{C}$ .

10. Tested initially and after any design or process changes that may affect these parameters.

11. Full device operation requires linear  $V_{CC}$  ramp from  $V_{DR}$  to  $V_{CC(\text{min.})} \geq 100\text{ }\mu\text{s}$  or stable at  $V_{CC(\text{min.})} \geq 100\text{ }\mu\text{s}$ .

12.  $\overline{BHE}, \overline{BLE}$  is the AND of both  $\overline{BHE}$  and  $\overline{BLE}$ . Chip can be deselected by either disabling the chip enable signals or by disabling both  $\overline{BHE}$  and  $\overline{BLE}$ .

## Switching Characteristics

Over the Operating Range

| Parameter <sup>[13]</sup>          | Description  | 55 ns |     | 70 ns |     | Unit |
|------------------------------------|--|-------|-----|-------|-----|------|
|                                    |  | Min   | Max | Min   | Max |      |
| <b>Read Cycle</b>                  |  |       |     |       |     |      |
| t <sub>RC</sub>                    | Read cycle time  | 55    | –   | 70    | –   | ns   |
| t <sub>AA</sub>                    | Address to data valid  | –     | 55  | –     | 70  | ns   |
| t <sub>OHA</sub>                   | Data hold from address change  | 10    | –   | 10    | –   | ns   |
| t <sub>ACE</sub>                   | $\overline{CE}_1$ LOW and CE <sub>2</sub> HIGH to data valid                 | –     | 55  | –     | 70  | ns   |
| t <sub>DOE</sub>                   | $\overline{OE}$ LOW to data valid  | –     | 25  | –     | 35  | ns   |
| t <sub>LZOE</sub>                  | $\overline{OE}$ LOW to low Z <sup>[14]</sup>                                 | 5     | –   | 5     | –   | ns   |
| t <sub>HZOE</sub>                  | $\overline{OE}$ HIGH to high Z <sup>[14, 15]</sup>                           | –     | 20  | –     | 25  | ns   |
| t <sub>LZCE</sub>                  | $\overline{CE}_1$ LOW and CE <sub>2</sub> HIGH to low Z <sup>[14]</sup>      | 10    | –   | 10    | –   | ns   |
| t <sub>HZCE</sub>                  | $\overline{CE}_1$ HIGH and CE <sub>2</sub> LOW to high Z <sup>[14, 15]</sup> | –     | 20  | –     | 25  | ns   |
| t <sub>PU</sub>                    | $\overline{CE}_1$ LOW and CE <sub>2</sub> HIGH to power-up                   | 0     | –   | 0     | –   | ns   |
| t <sub>PD</sub>                    | $\overline{CE}_1$ HIGH and CE <sub>2</sub> LOW to power-down                 | –     | 55  | –     | 70  | ns   |
| t <sub>DBE</sub>                   | $\overline{BLE}/\overline{BHE}$ LOW to data valid                            | –     | 55  | –     | 70  | ns   |
| t <sub>LZBE</sub>                  | $\overline{BLE}/\overline{BHE}$ LOW to low Z <sup>[14]</sup>                 | 10    | –   | 10    | –   | ns   |
| t <sub>HZBE</sub>                  | $\overline{BLE}/\overline{BHE}$ HIGH to high Z <sup>[14, 15]</sup>           | –     | 20  | –     | 25  | ns   |
| <b>Write Cycle <sup>[16]</sup></b> |  |       |     |       |     |      |
| t <sub>WC</sub>                    | Write cycle time   | 55    | –   | 70    | –   | ns   |
| t <sub>SCE</sub>                   | $\overline{CE}_1$ LOW and CE <sub>2</sub> HIGH to write end                  | 40    | –   | 60    | –   | ns   |
| t <sub>AW</sub>                    | Address setup to write end   | 40    | –   | 60    | –   | ns   |
| t <sub>HA</sub>                    | Address hold from write end  | 0     | –   | 0     | –   | ns   |
| t <sub>SA</sub>                    | Address setup to write start   | 0     | –   | 0     | –   | ns   |
| t <sub>PWE</sub>                   | $\overline{WE}$ pulse width  | 40    | –   | 45    | –   | ns   |
| t <sub>BW</sub>                    | $\overline{BLE}/\overline{BHE}$ LOW to write end                             | 40    | –   | 60    | –   | ns   |
| t <sub>SD</sub>                    | Data setup to write end  | 25    | –   | 30    | –   | ns   |
| t <sub>HD</sub>                    | Data hold from write end   | 0     | –   | 0     | –   | ns   |
| t <sub>HZWE</sub>                  | $\overline{WE}$ LOW to high-Z <sup>[14, 15]</sup>                            | –     | 20  | –     | 25  | ns   |
| t <sub>LZWE</sub>                  | $\overline{WE}$ HIGH to low-Z <sup>[14]</sup>                                | 10    | –   | 10    | –   | ns   |

### Notes

13. Test conditions for all parameters other than Tri-state parameters assume signal transition time of 1 ns/V, timing reference levels of  $V_{CC(typ)}/2$ , input pulse levels of 0 to  $V_{CC(typ)}$ , and output loading of the specified  $I_{OL}/I_{OH}$  as shown in the "AC Test Loads and Waveforms" section.

14. At any temperature and voltage condition, t<sub>HZCE</sub> is less than t<sub>LZCE</sub>, t<sub>HZBE</sub> is less than t<sub>LZBE</sub>, t<sub>HZOE</sub> is less than t<sub>LZOE</sub>, and t<sub>HZWE</sub> is less than t<sub>LZWE</sub> for any device.

15. t<sub>HZOE</sub>, t<sub>HZCE</sub>, t<sub>HZBE</sub>, and t<sub>HZWE</sub> transitions are measured when the outputs enter a high impedance state.

16. The internal Write time of the memory is defined by the overlap of  $\overline{WE}$ ,  $\overline{CE}_1 = V_{IL}$ ,  $\overline{BHE}$  and/or  $\overline{BLE} = V_{IL}$ , and  $CE_2 = V_{IH}$ . All signals must be ACTIVE to initiate a write and any of these signals can terminate a write by going INACTIVE. The data input setup and hold timing should be referenced to the edge of the signal that terminates the Write.

### Switching Waveforms

Figure 5. Read Cycle 1 (Address Transition Controlled) [17, 18]





Figure 6. Read Cycle 2 ( $\overline{OE}$  Controlled) [18, 19]




**Notes**

- 17. The device is continuously selected.  $\overline{OE}$ ,  $\overline{CE}_1$  =  $V_{IL}$ ,  $\overline{BHE}$  and/or  $\overline{BLE}$  =  $V_{IL}$ , and  $CE_2$  =  $V_{IH}$ .
- 18.  $\overline{WE}$  is HIGH for read cycle.
- 19. Address valid prior to or coincident with  $\overline{CE}_1$ ,  $\overline{BHE}$ ,  $\overline{BLE}$  transition LOW and  $CE_2$  transition HIGH.



Switching Waveforms (continued)

Figure 7. Write Cycle 1 ( $\overline{WE}$  Controlled) [20, 21, 22]



Notes

20. The internal Write time of the memory is defined by the overlap of  $\overline{WE}$ ,  $\overline{CE}_1 = V_{IL}$ ,  $\overline{BHE}$  and/or  $\overline{BLE} = V_{IL}$ , and  $CE_2 = V_{IH}$ . All signals must be ACTIVE to initiate a write and any of these signals can terminate a write by going INACTIVE. The data input setup and hold timing should be referenced to the edge of the signal that terminates the Write.

21. Data I/O is high-impedance if  $\overline{OE} = V_{IH}$ .

22. If  $\overline{CE}_1$  goes HIGH and  $CE_2$  goes LOW simultaneously with  $\overline{WE} = V_{IH}$ , the output remains in a high-impedance state.

23. During this period, the I/Os are in output state and input signals should not be applied.

Switching Waveforms (continued)

Figure 8. Write Cycle 2 ( $\overline{CE}_1$  or  $CE_2$  Controlled) [24, 25, 26]





Figure 9. Write Cycle 3 ( $\overline{WE}$  Controlled,  $\overline{OE}$  LOW) [26]



Notes

24. The internal Write time of the memory is defined by the overlap of  $\overline{WE}$ ,  $\overline{CE}_1 = V_{IL}$ ,  $\overline{BHE}$  and/or  $\overline{BLE} = V_{IL}$ , and  $CE_2 = V_{IH}$ . All signals must be ACTIVE to initiate a write and any of these signals can terminate a write by going INACTIVE. The data input setup and hold timing should be referenced to the edge of the signal that terminates the Write.


25. Data I/O is high-impedance if  $\overline{OE} = V_{IH}$ .

26. If  $\overline{CE}_1$  goes HIGH and  $CE_2$  goes LOW simultaneously with  $\overline{WE} = V_{IH}$ , the output remains in a high-impedance state.

27. During this period, the I/Os are in output state and input signals should not be applied.

Switching Waveforms (continued)

Figure 10. Write Cycle 4 ( $\overline{\text{BHE}}/\overline{\text{BLE}}$  Controlled,  $\overline{\text{OE}}$  LOW) <sup>[28]</sup>



Notes

- 28. If  $\overline{\text{CE}}_1$  goes HIGH and  $\text{CE}_2$  goes LOW simultaneously with  $\overline{\text{WE}} = V_{IH}$ , the output remains in a high-impedance state.
- 29. During this period, the I/Os are in output state and input signals should not be applied.

**Truth Table**


| $\overline{CE}_1$ | $CE_2$ | $\overline{WE}$ | $\overline{OE}$ | $\overline{BHE}$ | $\overline{BLE}$ | Inputs/Outputs   | Mode                | Power                |
|-------------------|--------|-----------------|-----------------|------------------|------------------|--|---------------------|----------------------|
| H                 | X      | X               | X               | X                | X                | High Z   | Deselect/Power-down | Standby ( $I_{SB}$ ) |
| X                 | L      | X               | X               | X                | X                | High Z   | Deselect/Power-down | Standby ( $I_{SB}$ ) |
| X                 | X      | X               | X               | H                | H                | High Z   | Deselect/Power-down | Standby ( $I_{SB}$ ) |
| L                 | H      | H               | L               | L                | L                | Data out ( $I/O_0$ – $I/O_{15}$ )                                  | Read                | Active ( $I_{CC}$ )  |
| L                 | H      | H               | L               | H                | L                | High Z ( $I/O_8$ – $I/O_{15}$ );<br>Data out ( $I/O_0$ – $I/O_7$ ) | Read                | Active ( $I_{CC}$ )  |
| L                 | H      | H               | L               | L                | H                | Data out ( $I/O_8$ – $I/O_{15}$ );<br>High Z ( $I/O_0$ – $I/O_7$ ) | Read                | Active ( $I_{CC}$ )  |
| L                 | H      | L               | X               | L                | L                | Data in ( $I/O_0$ – $I/O_{15}$ )                                   | Write               | Active ( $I_{CC}$ )  |
| L                 | H      | L               | X               | H                | L                | High Z ( $I/O_8$ – $I/O_{15}$ );<br>Data in ( $I/O_0$ – $I/O_7$ )  | Write               | Active ( $I_{CC}$ )  |
| L                 | H      | L               | X               | L                | H                | Data in ( $I/O_8$ – $I/O_{15}$ );<br>High Z ( $I/O_0$ – $I/O_7$ )  | Write               | Active ( $I_{CC}$ )  |
| L                 | H      | H               | H               | L                | H                | High Z   | Output disabled     | Active ( $I_{CC}$ )  |
| L                 | H      | H               | H               | H                | L                | High Z   | Output disabled     | Active ( $I_{CC}$ )  |
| L                 | H      | H               | H               | L                | L                | High Z   | Output disabled     | Active ( $I_{CC}$ )  |

## Ordering Information

| Speed (ns) | Ordering Code        | Package Diagram | Package Type                             | Operating Range |
|------------|----------------------|-----------------|--|-----------------|
| 55         | CY62167DV30LL-55BVI  | 51-85178        | 48-ball FBGA (8 × 9.5 × 1 mm)            | Industrial      |
|            | CY62167DV30LL-55BVXI |                 | 48-ball FBGA (8 × 9.5 × 1 mm) Pb-free    |                 |
|            | CY62167DV30LL-55ZXI  | 51-85183        | 48-pin TSOP I (12 × 18.4 × 1 mm) Pb-free |                 |
| 70         | CY62167DV30LL-70BVI  | 51-85178        | 48-ball FBGA (8 × 9.5 × 1 mm)            |                 |


Please contact your local Cypress sales representative for availability of these parts

## Ordering Code Definitions



Package Diagrams


Figure 11. 48-ball VFBGA (8 × 9.5 × 1 mm) BV48B Package Outline, 51-85178



51-85178 \*C

Package Diagrams (continued)

Figure 12. 48-pin TSOP I (12 x 18.4 x 1 mm) Z48A Package Outline, 51-85183



51-85183 \*C

## Acronyms

| Acronym | Description                             |
|---------|---|
| CMOS    | Complementary Metal Oxide Semiconductor |
| I/O     | Input/Output                            |
| SRAM    | Static Random Access Memory             |
| TSOP    | Thin Small Outline Package              |
| VFBGA   | Very Fine-Pitch Ball Grid Array         |

## Document Conventions

### Units of Measure

| Symbol | Unit of Measure |
|--------|-----------------|
| °C     | degrees Celsius |
| MHz    | megahertz       |
| μA     | microampere     |
| mA     | milliampere     |
| ns     | nanosecond      |
| Ω      | ohm             |
| pF     | picofarad       |
| V      | volt            |
| W      | watt            |



Document History Page

| Document Title: CY62167DV30 MoBL®, 16-Mbit (1 M x 16) Static RAM<br>Document Number: 38-05328 |         |                 |                 |  |
|---|---------|-----------------|-----------------|--|
| Revision  | ECN     | Orig. of Change | Submission Date | Description of Change  |
| **  | 118408  | GUG             | 09/30/02        | New data sheet.  |
| *A  | 123692  | DPM             | 02/11/03        | Changed status from Advanced to Preliminary.<br>Added package diagram  |
| *B  | 126555  | DPM             | 04/25/03        | Minor change: Changed Sunset Owner from DPM to HRT   |
| *C  | 127841  | XRJ             | 09/10/03        | Added 48 TSOP I package  |
| *D  | 205701  | AJU             | See ECN         | Changed BYTE pin usage description for 48 TSOP I package   |
| *E  | 238050  | KKV/AJU         | See ECN         | Replaced 48-ball VFBGA package diagram; Modified Package Name in Ordering Information table from BV48A to BV48B  |
| *F  | 304054  | PCI             | See ECN         | Added 45-ns Speed Bin in AC, DC and Ordering Information tables<br>Added Footnote #12 on page #4<br>Added Pb-free packages on page # 10  |
| *G  | 492895  | VKN             | See ECN         | Modified datasheet to explain x8 configurability.<br>Removed L power bin from the product offering<br>Updated Ordering Information Table   |
| *H  | 2896036 | AJU             | 03/19/10        | Removed 45-ns. Removed inactive parts from Ordering Information.<br>Updated Packaging Information<br>Updated links in Sales, Solutions, and Legal Information.   |
| *I  | 3067267 | RAME            | 11/08/10        | Updated datasheet as per new template<br>Added <a href="#">Ordering Code Definitions</a> .<br>Added <a href="#">Acronyms</a> and <a href="#">Units of Measure</a> .<br>Updated all table notes to footnote.<br>Package diagram updated 51-85178 from ** to *A  |
| *J  | 3329789 | RAME            | 07/27/11        | Removed references to AN1064 SRAM system guidelines.<br>Updated template according to current CY standards.  |
| *K  | 4108382 | AJU             | 08/29/2013      | Updated <a href="#">Pin Configurations</a> :<br>Removed the note “Ball H6 for the FBGA package can be used to upgrade to a 32M density” and its reference in <a href="#">Figure 1</a> .<br>Updated <a href="#">Package Diagrams</a> :<br>spec 51-85178 – Changed revision from *A to *C.<br>Updated in new template. |
| *L  | 4192919 | VINI            | 11/15/2013      | No technical updates.<br>Completing Sunset Review.   |
| *M  | 4574377 | VINI            | 11/19/2014      | Added related documentation hyperlink in page 1.   |

## Sales, Solutions, and Legal Information

### Worldwide Sales and Design Support

Cypress maintains a worldwide network of offices, solution centers, manufacturer's representatives, and distributors. To find the office closest to you, visit us at [Cypress Locations](#).

#### Products

|  |  |
|--|--|
| <a href="#">Automotive</a>                   | <a href="#">cypress.com/go/automotive</a>                                      |
| <a href="#">Clocks &amp; Buffers</a>         | <a href="#">cypress.com/go/clocks</a>  |
| <a href="#">Interface</a>                    | <a href="#">cypress.com/go/interface</a>                                       |
| <a href="#">Lighting &amp; Power Control</a> | <a href="#">cypress.com/go/powerpsoc</a><br><a href="#">cypress.com/go/plc</a> |
| <a href="#">Memory</a>                       | <a href="#">cypress.com/go/memory</a>  |
| <a href="#">PSoC</a>                         | <a href="#">cypress.com/go/psoc</a>  |
| <a href="#">Touch Sensing</a>                | <a href="#">cypress.com/go/touch</a>   |
| <a href="#">USB Controllers</a>              | <a href="#">cypress.com/go/USB</a>   |
| <a href="#">Wireless/RF</a>                  | <a href="#">cypress.com/go/wireless</a>  |

#### PSoC<sup>®</sup> Solutions

[psoc.cypress.com/solutions](#)  
[PSoC 1](#) | [PSoC 3](#) | [PSoC 4](#) | [PSoC 5LP](#)

#### Cypress Developer Community

[Community](#) | [Forums](#) | [Blogs](#) | [Video](#) | [Training](#)

#### Technical Support

[cypress.com/go/support](#)

---

© Cypress Semiconductor Corporation, 2002-2014. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Infineon:](#)

[CY62167DV30LL-55BVXI](#) [CY62167DV30LL-55BVXIT](#) [CY62167DV30LL-55ZXI](#) [CY62167DV30LL-55ZXIT](#)  
[CY62167DV30LL-70BVI](#) [CY62167DV30LL-70BVIT](#)