SMA Fixed Attenuator

DC to 6000 MHz 50Ω **2W** 5dB

Maximum Ratings

Operating Temperature -45°C to 100°C -55°C to 100°C Storage Temperature

Permanent damage may occur if any of these limits are exceeded

Features

- wideband coverage, DC to 6000 MHz
- 2 watt rating
- rugged unibody construction
- · off-the-shelf availability
- · very low cost

Applications

- impedance matching
- · signal level adjustment

VAT-5W2+




Generic photo used for illustration purposes only CASE STYLE: DC1066

Connectors Model SMA VAT-5W2+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing



Outline Dimensions (inch)

wt	Е	D	В
grams	.312	1.43	.74
11.4	7.92	36.32	18.80


Electrical Specifications


FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **					VSWR (:1)		MAX. INPUT POWER	
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f _L f _U	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	5±0.3	0.20	0.10	0.15	0.35	1.10 1.20	1.40 1.50	1.65	2.0

^{*} Attenuation varies by 0.3 dB max. over temperature.

Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)	
10.00	4.99	1.00	
100.00	5.03	1.01	
1000.00	5.16	1.05	
2000.00	5.22	1.06	
3000.00	5.31	1.04	
4000.00	5.41	1.03	
4500.00	5.42	1.10	
5000.00	5.45	1.20	
5500.00	5.57	1.32	
6000.00	5.68	1.51	





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

^{**} Flatness= variation over band divided by 2.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: VAT-5W2+