



Note: This datasheet may be out of date

Please download the latest datasheet of TZV2Z030A110R00 from the official website of Murata Manufacturing

http://www.murata.com/en-eu/products/productdetail?partno=TZV2Z030A110R00

### TZV2Z030A110R00










## Appearance & Shape









### Features

- 1. Small size with external dimensions of
- 2.3(W)x3.2(L)x1.45max.(H)mm.
- 2. Unique construction with no plastic material provides superior soldering heat resistance to maintain excellent characteristic performance after reflow soldering.
- 3. Designed for automatic placement in surface mount pplications.
- 4. Funnel shaped metal case enables in-process automatic



# **Packaging Information**

Packaging	Specifications	Minimum Order Quantity
R00	180mm Embossed Tape	2000

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/

Last updated :2017/10/30




Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ TZV2Z030A110R00 \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$ 

Co., Ltd. http://www.murata.com/en-eu/products/productdetail?partno=TZV2Z030A110R00

## TZV2Z030A110R00



Shape	SMD	
Operating Temperature Range	-25°C to 85°C	
Thickness	1.45mm	
Thickness Tolerance	max.	
Rated Voltage	25Vdc	
Cmin.(max.)	1.5pF	
Cmax.	3pF	
Cmax. Tolerance	+100/-0%	
Adjustment Direction	Тор	
Soldering Method	Reflow Soldering Iron	
тс	NP0±300ppm/°C	
Q	300min. at 1MHz, Cmax.	
Withstanding Voltage	55Vdc	
Insulation Resistance(min.)	10000ΜΩ	
Torque	1.0 to 9.8mNm	
Mass	0.04g	

2 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: http://www.murata.com/

### Co., Ltd. http://www.murata.com/en-eu/products/productdetail?partno=TZV2Z030A110R00

## TZV2Z030A110R00







Constructions

Temp. Coeff. Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: http://www.murata.com/