

Specification Sheet

Part Number: 150-74890



Fir tree design can be used with a wide variety of applications. Disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.

Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.

2-Piece Cable Tie/Fir Tree Mount, 6.0" Long, Mounting Hole Diameter 0.23" - 0.24", PA66HS, Black, 500/pkg

Article Number 150-74890

Type T30RFT6D10

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.

Short Description 2-Piece Cable Tie/Fir Tree Mount, 6.0" Long, Mounting Hole Diameter 0.23" - 0.24", PA66HS, Black, 500/pkg

Global Part Name

T30RFT6D10-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial) 30.0

Minimum Tensile Strength (Metric) 135

Length L (Imperial) 6.0

Length L (Metric) 150

Fixation Method Fir Tree

Identification Plate Position none

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14

Width W (Metric) 3.5

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Max (Imperial) 1.2

Bundle Diameter Max (Metric) 32.0

Height H (Imperial) 0.04

Height H (Metric) 1.1

Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.12
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	4.3
Mounting Hole Diameter D (Imperial)	0.23 - 0.24
Mounting Hole Diameter D (Metric)	5.8 - 6.2 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.27
Mounting Hole Diameter D Max (Metric)	6.2
Disc Diameter (Metric)	9.8
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL 94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HellermannTyton:](#)

[150-74890](#)