

# MKYDT1-8017



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue):380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 185g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: plastic

## MKTFS-2



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 189g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: Aluminum

# MKYDT1-10



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue):380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 239g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: iron

# MKYDT1-18



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 343g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: Aluminum

## MKYDT1-1F



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 215 g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: iron

## MKYDT1-1P



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 85 g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: plastic

## MKYDT1-2



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 151g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: Aluminum



# MKYDT1-201



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue):380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 126g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: plastic



## MKYDT1-8012



Max. Voltage: 380V

Rated Current: 10A

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 86g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: plastic

## MKEKW-5A-B



Max. Voltage: 380V

**Rated Current: 5A**

Rated Working Voltage (Ue): 380VAC/220VDC

Rated insulation voltage (Ui): 380V

Net Weight: 129g

Mechanical Life: >10000

Standart: GB14048.5-2001 –

Material of rind: Aluminum