

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Safety data sheet according to Regulation (EC) 2020/878

Revision date 28/09/2023

Revision Number 0.44

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name RS Pro Red Gloss Spray Paint
Product Code(s) 764-3049, ZP
Safety data sheet number 00894
Unique Formula Identifier (UFI) 0WJ7-P03G-400X-7SMQ
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Paint
Uses advised against No specific uses advised against are identified

1.3. Details of the supplier of the safety data sheet

Supplier

RS Components Ltd
Birchington Road
Corby
Northants
NN17 9RS
+44 (0) 845 850 9900
RCustomerServicesUK@rs-components.com

RS Components Ltd
Glennview Industrial Estate
Herberton Road
Rialto
Dublin 12
+353 (0) 1 415 3100
enquiries.ie@rs-components.com

For further information, please contact

E-mail address RCustomerServicesUK@rs-components.com

1.4. Emergency telephone number

Emergency Telephone POISON INFORMATION CENTRE (Beaumont Hospital, Republic of Ireland only) +353 (0)1 809 2166 (08:00 - 22:00)

Emergency Telephone -

+44 1235 239670 (24hr)
+44 (0) 1865 407333 (24hr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008 [CLP]

Aerosols	Category 1 - (H222, H229)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H336)

2.2. Label elements

Contains Acetone, xylene, butanone, 1-Methoxy-2-propanol



Signal word

Danger

Hazard statements

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing spray.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients**3.1 Substances**

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
Petroleum gases, liquefied 68476-85-7	30-60	No data available	270-704-2	Flam. Gas 1A (H220)	-	-	-
Acetone 67-64-1	10-30	01-2119471330-49-00 00	200-662-2	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	-	-
xylene 1330-20-7	5-10	01-2119488216-32-00 00	215-535-7	Aquatic Chronic 3 (H412) Asp. Tox. 1 (H304) Flam. Liq. 3 (H226) Acute Tox. 4 (H332) STOT RE 2 (H373) Eye Irrit. 2 (H319) Skin Irrit. 2 (H315) Acute Tox. 4 (H312) STOT SE 3 (H335)	-	-	-
butanone 78-93-3	5-10	01-2119457290-43-00 00	201-159-0	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	-	-
2-Methoxy-1-methylethyl acetate 108-65-6	5-10	01-2119475791-29-00 00	203-603-9	Flam. Liq. 3 (H226)	-	-	-
1-Methoxy-2-propanol 107-98-2	1-5	01-2119457435-35-00 00	203-539-1	Flam. Liq. 3 (H226) STOT SE 3 (H336)	-	-	-

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

Chemical name	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Acetone 67-64-1	5800	15700	100.2	No data available	No data available
xylene 1330-20-7	3500	4350	No data available	No data available	No data available
butanone 78-93-3	2483	5000	No data available	34.5018	No data available
2-Methoxy-1-methylethyl acetate 108-65-6	8532	5000	24	No data available	No data available
1-Methoxy-2-propanol 107-98-2	5000	13000	No data available	34.1234	No data available

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention. If symptoms persist, call a doctor. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Use personal protective equipment as required. See section 8 for more information.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation. Coughing and/ or wheezing. Difficulty in breathing.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists.
---	--

Containers may explode when heated.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep out of the reach of children.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Belgium	Bulgaria	Croatia
Petroleum gases, liquefied 68476-85-7	-	-	TWA: 1000 ppm TWA: 1826 mg/m ³	-	TWA: 1000 ppm TWA: 1750 mg/m ³ STEL: 1250 ppm STEL: 2180 mg/m ³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL 2000 ppm STEL 4800 mg/m ³	TWA: 246 ppm TWA: 594 mg/m ³ STEL: 492 ppm STEL: 1187 mg/m ³	STEL: 1400 mg/m ³ TWA: 600 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³
2-Methoxy-1-methylethyl acetate 108-65-6	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ *	TWA: 50 ppm TWA: 275 mg/m ³ STEL 100 ppm STEL 550 mg/m ³ H*	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ D*	STEL: 100 ppm STEL: 550.0 mg/m ³ TWA: 50 ppm TWA: 275.0 mg/m ³ K*	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ *
xylene 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *	TWA: 50 ppm TWA: 221 mg/m ³ STEL 100 ppm STEL 442 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ D*	STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221.0 mg/m ³ K*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *
butanone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 100 ppm TWA: 295 mg/m ³ STEL 200 ppm STEL 590 mg/m ³ H*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	STEL: 885 mg/m ³ TWA: 590 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³
1-Methoxy-2-propanol 107-98-2	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ *	TWA: 50 ppm TWA: 187 mg/m ³ STEL 50 ppm STEL 187 mg/m ³ Ceiling: 50 ppm Ceiling: 187 mg/m ³ H*	TWA: 50 ppm TWA: 184 mg/m ³ STEL: 100 ppm STEL: 369 mg/m ³ D*	STEL: 150 ppm STEL: 568.0 mg/m ³ TWA: 100 ppm TWA: 375.0 mg/m ³ K*	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³
Chemical name	Cyprus	Czech Republic	Denmark	Estonia	Finland

Petroleum gases, liquefied 68476-85-7	-	TWA: 1800 mg/m ³ Ceiling: 4000 mg/m ³	-	-	-
Acetone 67-64-1	* TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 800 mg/m ³ Ceiling: 1500 mg/m ³	TWA: 250 ppm TWA: 600 mg/m ³ STEL: 500 ppm STEL: 1200 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 630 ppm STEL: 1500 mg/m ³
2-Methoxy-1-methylethyl acetate 108-65-6	* STEL: 100 ppm STEL: 550 mg/m ³ TWA: 50 ppm TWA: 275 mg/m ³	TWA: 270 mg/m ³ Ceiling: 550 mg/m ³ D*	TWA: 50 ppm TWA: 275 mg/m ³ H* STEL: 550 mg/m ³ STEL: 100 ppm	S+ TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ A*	TWA: 50 ppm TWA: 270 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ iho*
xylene 1330-20-7	* STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 200 mg/m ³ Ceiling: 400 mg/m ³ D*	TWA: 25 ppm TWA: 109 mg/m ³ H* STEL: 442 mg/m ³ STEL: 100 ppm	TWA: 50 ppm TWA: 200 mg/m ³ STEL: 100 ppm STEL: 450 mg/m ³ A*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 440 mg/m ³ iho*
butanone 78-93-3	STEL: 300 ppm STEL: 900 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³	TWA: 600 mg/m ³ Ceiling: 900 mg/m ³	TWA: 50 ppm TWA: 145 mg/m ³ H* STEL: 900 mg/m ³ STEL: 300 ppm	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 20 ppm TWA: 60 mg/m ³ STEL: 100 ppm STEL: 300 mg/m ³ iho*
1-Methoxy-2-propanol 107-98-2	* STEL: 150 ppm STEL: 568 mg/m ³ TWA: 100 ppm TWA: 375 mg/m ³	TWA: 270 mg/m ³ Ceiling: 550 mg/m ³ D*	TWA: 50 ppm TWA: 185 mg/m ³ H* STEL: 568 mg/m ³ STEL: 150 ppm	S+ TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ A*	TWA: 100 ppm TWA: 370 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ iho*
Chemical name	France	Germany TRGS	Germany DFG	Greece	Hungary
Petroleum gases, liquefied 68476-85-7	-	-	-	TWA: 1250 ppm TWA: 2250 mg/m ³ STEL: 1250 ppm STEL: 2250 mg/m ³	-
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1000 ppm STEL: 2420 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³ Peak: 1000 ppm Peak: 2400 mg/m ³	TWA: 1780 mg/m ³ STEL: 3560 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³
2-Methoxy-1-methylethyl acetate 108-65-6	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ *	TWA: 50 ppm TWA: 270 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³ Peak: 50 ppm Peak: 270 mg/m ³	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ *	TWA: 275 mg/m ³ TWA: 50 ppm STEL: 550 mg/m ³ STEL: 100 ppm
xylene 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ *	TWA: 50 ppm TWA: 220 mg/m ³ H*	TWA: 50 ppm TWA: 220 mg/m ³ Peak: 100 ppm Peak: 440 mg/m ³ *	TWA: 100 ppm TWA: 435 mg/m ³ STEL: 150 ppm STEL: 650 mg/m ³ *	TWA: 221 mg/m ³ TWA: 50 ppm STEL: 442 mg/m ³ STEL: 100 ppm b*
butanone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ *	TWA: 200 ppm TWA: 600 mg/m ³ H*	TWA: 200 ppm TWA: 600 mg/m ³ Peak: 200 ppm Peak: 600 mg/m ³ *	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 600 mg/m ³ TWA: 200 ppm STEL: 900 mg/m ³ STEL: 300 ppm b*
1-Methoxy-2-propanol 107-98-2	TWA: 50 ppm TWA: 188 mg/m ³ STEL: 100 ppm STEL: 375 mg/m ³ *	TWA: 100 ppm TWA: 370 mg/m ³	TWA: 100 ppm TWA: 370 mg/m ³ Peak: 200 ppm Peak: 740 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 300 ppm STEL: 1080 mg/m ³ *	TWA: 375 mg/m ³ TWA: 100 ppm STEL: 568 mg/m ³ STEL: 150 ppm b*
Chemical name	Ireland	Italy MDLPS	Italy AIDII	Latvia	Lithuania

Petroleum gases, liquefied 68476-85-7	-	-	Simple asphyxiant	-	-
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 250 ppm TWA: 594 mg/m ³ STEL: 500 ppm STEL: 1187 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	STEL: 1000 ppm STEL: 2420 mg/m ³ TWA: 500 ppm TWA: 1210 mg/m ³
2-Methoxy-1-methylethyl acetate 108-65-6	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ Sk*	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ cute*	-	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ Ada*	STEL: 75 ppm STEL: 400 mg/m ³ TWA: 50 ppm TWA: 250 mg/m ³ O*
xylene 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Sk*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ cute*	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Ada*	STEL: 442 mg/m ³ STEL: 100 ppm TWA: 221 mg/m ³ TWA: 50 ppm O*
butanone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Sk*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³	TWA: 67 ppm TWA: 200 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	-
1-Methoxy-2-propanol 107-98-2	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ cute*	TWA: 50 ppm TWA: 184 mg/m ³ STEL: 100 ppm STEL: 368 mg/m ³	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ Ada*	STEL: 300 mg/m ³ STEL: 75 ppm TWA: 190 mg/m ³ TWA: 50 ppm O*
Chemical name	Luxembourg	Malta	Netherlands	Norway	Poland
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1 ppm STEL: 2420 mg/m ³	TWA: 125 ppm TWA: 295 mg/m ³ STEL: 156.25 ppm STEL: 368.75 mg/m ³	STEL: 1800 mg/m ³ TWA: 600 mg/m ³
2-Methoxy-1-methylethyl acetate 108-65-6	STEL: 100 ppm STEL: 550 mg/m ³ TWA: 50 ppm TWA: 275 mg/m ³ Peau*	STEL: 100 ppm STEL: 550 mg/m ³ skin* TWA: 50 ppm TWA: 275 mg/m ³	TWA: 100 ppm TWA: 550 mg/m ³	TWA: 50 ppm TWA: 270 mg/m ³ STEL: 75 ppm STEL: 337.5 mg/m ³ H*	STEL: 520 mg/m ³ TWA: 260 mg/m ³ skóra*
xylene 1330-20-7	STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³ Peau*	STEL: 100 ppm STEL: 442 mg/m ³ skin* TWA: 50 ppm TWA: 221 mg/m ³	TWA: 47.5 ppm TWA: 210 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ H*	TWA: 25 ppm TWA: 108 mg/m ³ STEL: 37.5 ppm STEL: 135 mg/m ³ H*	STEL: 200 mg/m ³ TWA: 100 mg/m ³ skóra*
butanone 78-93-3	STEL: 300 ppm STEL: 900 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³	STEL: 300 ppm STEL: 900 mg/m ³ TWA: 200 ppm TWA: 600 mg/m ³	TWA: 197 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ H*	TWA: 75 ppm TWA: 220 mg/m ³ STEL: 112.5 ppm STEL: 275 mg/m ³	STEL: 900 mg/m ³ TWA: 450 mg/m ³ skóra*
1-Methoxy-2-propanol 107-98-2	STEL: 150 ppm STEL: 568 mg/m ³ TWA: 100 ppm TWA: 375 mg/m ³ Peau*	STEL: 150 ppm STEL: 568 mg/m ³ skin* TWA: 100 ppm TWA: 375 mg/m ³	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 563 mg/m ³ H*	TWA: 50 ppm TWA: 180 mg/m ³ STEL: 75 ppm STEL: 225 mg/m ³ H*	STEL: 360 mg/m ³ TWA: 180 mg/m ³ skóra*
Chemical name	Portugal	Romania	Slovakia	Slovenia	Spain
Petroleum gases, liquefied 68476-85-7	TWA: 1000 ppm	-	-	-	TWA: 1000 ppm
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 750 ppm	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 2420 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³

2-Methoxy-1-methylethyl acetate 108-65-6	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ Cutânea*	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ P*	TWA: 50 ppm TWA: 275 mg/m ³ K* Ceiling: 550 mg/m ³	STEL: 100 ppm TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ K*	TWA: 50 ppm TWA: 275 mg/m ³ STEL: 100 ppm STEL: 550 mg/m ³ via dérmica*
xylene 1330-20-7	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ Cutânea*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ P*	TWA: 50 ppm TWA: 221 mg/m ³ K* Ceiling: 442 mg/m ³	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ K*	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ via dérmica*
butanone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ Ceiling: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ K*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³
1-Methoxy-2-propanol 107-98-2	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ P*	TWA: 100 ppm TWA: 375 mg/m ³ K* Ceiling: 568 mg/m ³	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ K*	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 568 mg/m ³ via dérmica*
Chemical name	Sweden		Switzerland	United Kingdom	
Petroleum gases, liquefied 68476-85-7	-		-	TWA: 1000 ppm TWA: 1750 mg/m ³ STEL: 1250 ppm STEL: 2180 mg/m ³	
Acetone 67-64-1	Vägledande KGV: 500 ppm Vägledande KGV: 1200 mg/m ³ NGV: 250 ppm NGV: 600 mg/m ³		TWA: 500 ppm TWA: 1200 mg/m ³ STEL: 1000 ppm STEL: 2400 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³	
2-Methoxy-1-methylethyl acetate 108-65-6	Bindande KGV: 100 ppm Bindande KGV: 550 mg/m ³ NGV: 50 ppm NGV: 275 mg/m ³ H*		TWA: 50 ppm TWA: 275 mg/m ³ STEL: 50 ppm STEL: 275 mg/m ³	TWA: 50 ppm TWA: 274 mg/m ³ STEL: 100 ppm STEL: 548 mg/m ³ Sk*	
xylene 1330-20-7	Bindande KGV: 100 ppm Bindande KGV: 442 mg/m ³ NGV: 50 ppm NGV: 221 mg/m ³ H*		TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 440 mg/m ³ H*	TWA: 50 ppm TWA: 220 mg/m ³ STEL: 100 ppm STEL: 441 mg/m ³ Sk*	
butanone 78-93-3	Bindande KGV: 300 ppm Bindande KGV: 900 mg/m ³ NGV: 50 ppm NGV: 150 mg/m ³		TWA: 200 ppm TWA: 590 mg/m ³ STEL: 200 ppm STEL: 590 mg/m ³ H*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*	
1-Methoxy-2-propanol 107-98-2	Bindande KGV: 150 ppm Bindande KGV: 568 mg/m ³ NGV: 50 ppm NGV: 190 mg/m ³ H*		TWA: 100 ppm TWA: 360 mg/m ³ STEL: 200 ppm STEL: 720 mg/m ³	TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³ Sk*	

Biological occupational exposure limits This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Chemical name	European Union	Austria	Bulgaria	Croatia	Czech Republic
Acetone 67-64-1	-	-	80 mg/L - urine (Acetone) - at the end of exposure or end of work shift	20.0 mg/L - blood (Acetone) - at the end of the work shift 20.0 mg/g Creatinine	-

				- urine (Acetone) - at the end of the work shift	
xylene 1330-20-7	-	1.5 g/L (urine - Methylhippuric acid after end of work day, at the end of a work week/end of the shift)	-	1.50 mg/L - blood (Xylene) - at the end of the work shift 1.50 g/g Creatinine - urine (Methylhippuric acid) - at the end of the work shift	820 µmol/mmol Creatinine (urine - Methylhippuric acid end of shift) 1400 mg/g Creatinine (urine - Methylhippuric acid end of shift)
butanone 78-93-3	-	-	-	2.6 mg/g Creatinine - urine (Ethyl methyl ketone) - at the end of the work shift	-
Chemical name	Denmark	Finland	France	Germany DFG	Germany TRGS
Acetone 67-64-1	-	-	100 mg/L - urine (Acetone) - end of shift	80 mg/L (urine - Acetone end of shift) 50 mg/L - BAT (end of exposure or end of shift) urine 2.5 mg/L - BAR (end of exposure or end of shift) urine	80 mg/L (urine - Acetone end of shift)
xylene 1330-20-7	-	5.0 mmol/L (urine - Methylhippuric acid after the shift)	1500 mg/g creatinine - urine (Methylhippuric acid) - end of shift	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of shift) 2000 mg/L - BAT (end of exposure or end of shift) urine	2000 mg/L (urine - Methylhippuric(tolur-)acid (all isomers) end of shift)
butanone 78-93-3	-	-	2 mg/L - urine (Methylethylketone) - end of shift	2 mg/L (urine - 2-Butanone end of shift) 2 mg/L - BAT (end of exposure or end of shift) urine	2 mg/L (urine - 2-Butanone end of shift)
1-Methoxy-2-propanol 107-98-2	-	-	-	15 mg/L (urine - 1-Methoxypropan-2-ol end of shift) 15 mg/L - BAT (end of exposure or end of shift) urine	15 mg/L (urine - 1-Methoxypropan-2-ol end of shift)
Chemical name	Hungary	Ireland	Italy MDLPS	Italy AIDII	
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-	25 mg/L - urine (Acetone) - end of shift	
xylene 1330-20-7	1500 mg/g Creatinine (urine - Methyl hippuric acid end of shift) 860 µmol/mmol Creatinine (urine - Methyl hippuric acid end of shift)	1.5 g/g Creatinine (urine - Methylhippuric acids end of shift)	-	1.5 g/g Creatinine - urine (Methylhippuric acid) - end of shift	
butanone 78-93-3	-	70 µmol/L (urine - Butan-2-one post shift)	-	2 mg/L - urine (MEK) - end of shift	
Chemical name	Latvia	Luxembourg	Romania	Slovakia	
Acetone 67-64-1	-	-	50 mg/L - urine (Acetone) - end of shift	80 mg/L (urine - Acetone end of exposure or work shift)	
xylene	-	-	3 g/L - urine	1.5 mg/L (blood - Xylene)	

1330-20-7			(Methylhippuric acid) - end of shift	end of exposure or work shift) 2000 mg/L (urine - Methylhippuric acid end of exposure or work shift)
butanone 78-93-3	-	-	2 mg/L - urine (Methylethylketone) - end of shift	-
Chemical name	Slovenia	Spain	Switzerland	United Kingdom
Acetone 67-64-1	80.0 mg/L - urine (Acetone) - at the end of the work shift	50 mg/L (urine - Acetone end of shift)	50 mg/L (urine - Acetone end of shift) 0.86 mmol/L (urine - Acetone end of shift)	-
xylene 1330-20-7	2 g/L - urine (Methylhippuric acid (all isomers)) - at the end of the work shift	1 g/g Creatinine (urine - Methylhippuric acids end of shift)	2 g/L (urine - Methylhippuric acid end of shift)	650 mmol/mol creatinine - urine (Methyl hippuric acid) - post shift
butanone 78-93-3	2 mg/L - urine (2-Butanone) - at the end of the work shift	2 mg/L (urine - Methyl ethyl ketone end of shift)	2 mg/L (urine - 2-Butanone end of shift, before subsequent shift or 16 hour) 27.7 µmol/L (urine - 2-Butanone end of shift, before subsequent shift or 16 hour)	70 µmol/L - urine (Butan-2-one) - post shift
1-Methoxy-2-propanol 107-98-2	15 mg/L - urine (1-Methoxypropan-2-ol) - at the end of the work shift	-	20 mg/L (urine - 1-Methoxypropanol-2 end of shift) 221.9 µmol/L (urine - 1-Methoxypropanol-2 end of shift)	-

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
Petroleum gases, liquefied 68476-85-7	-	23.4 mg/kg bw/day [4] [6]	-
Acetone 67-64-1	-	186 mg/kg bw/day [4] [6]	1210 mg/m ³ [4] [6] 2420 mg/m ³ [5] [7]
2-Methoxy-1-methylethyl acetate 108-65-6	-	796 mg/kg bw/day [4] [6]	275 mg/m ³ [4] [6] 550 mg/m ³ [5] [7]
xylene 1330-20-7	-	212 mg/kg bw/day [4] [6]	221 mg/m ³ [4] [6] 442 mg/m ³ [4] [7] 221 mg/m ³ [5] [6] 442 mg/m ³ [5] [7]
butanone 78-93-3	-	1161 mg/kg bw/day [4] [6]	600 mg/m ³ [4] [6]
1-Methoxy-2-propanol 107-98-2	-	183 mg/kg bw/day [4] [6]	369 mg/m ³ [4] [6] 553.5 mg/m ³ [4] [7] 553.5 mg/m ³ [5] [7]

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
Acetone 67-64-1	62 mg/kg bw/day [4] [6]	-	200 mg/m ³ [4] [6]

Chemical name	Oral	Dermal	Inhalation
2-Methoxy-1-methylethyl acetate 108-65-6	36 mg/kg bw/day [4] [6]	-	33 mg/m ³ [4] [6] 33 mg/m ³ [5] [6]
xylene 1330-20-7	12.5 mg/kg bw/day [4] [6]	-	65.3 mg/m ³ [4] [6] 260 mg/m ³ [4] [7] 65.3 mg/m ³ [5] [6] 260 mg/m ³ [5] [7]
butanone 78-93-3	31 mg/kg bw/day [4] [6]	-	106 mg/m ³ [4] [6]
1-Methoxy-2-propanol 107-98-2	33 mg/kg bw/day [4] [6]	-	43.9 mg/m ³ [4] [6]

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
Acetone 67-64-1	10.6 mg/L	21 mg/L	1.06 mg/L	-	-
2-Methoxy-1-methylethyl acetate 108-65-6	0.635 mg/L	6.35 mg/L	0.0635 mg/L	-	-
xylene 1330-20-7	0.327 mg/L	0.327 mg/L	0.327 mg/L	-	-
butanone 78-93-3	55.8 mg/L	55.8 mg/L	55.8 mg/L	-	-
1-Methoxy-2-propanol 107-98-2	10 mg/L	100 mg/L	1 mg/L	-	-

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Acetone 67-64-1	30.4 mg/kg sediment dw	3.04 mg/kg sediment dw	100 mg/L	29.5 mg/kg soil dw	-
2-Methoxy-1-methylethyl acetate 108-65-6	3.29 mg/kg sediment dw	0.329 mg/kg sediment dw	100 mg/L	0.29 mg/kg soil dw	-
xylene 1330-20-7	12.46 mg/kg sediment dw	12.46 mg/kg sediment dw	6.58 mg/L	2.31 mg/kg soil dw	-
butanone 78-93-3	284.74 mg/kg sediment dw	284.7 mg/kg sediment dw	709 mg/L	22.5 mg/kg soil dw	1000 mg/kg food
1-Methoxy-2-propanol 107-98-2	52.3 mg/kg sediment dw	5.2 mg/kg sediment dw	100 mg/L	4.59 mg/kg soil dw	-

8.2. Exposure controls**Engineering controls**

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment**Eye/face protection**

Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures.

Hand protection

Impervious gloves. Wear suitable gloves.

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.
Environmental exposure controls	No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Aerosol
Appearance	Aerosol
Colour	red
Odour	Solvent.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	-40 °C	Closed cup
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	0.735	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

9.2.1. Information with regards to physical hazard classes
No information available

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Excessive heat.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness. Harmful by inhalation. (based on components).
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation. Coughing and/ or wheezing.

Acute toxicity**Numerical measures of toxicity**

No information available

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	4,961.10 mg/kg
ATEmix (dermal)	4,678.30 mg/kg
ATEmix (inhalation-gas)	64,285.70 ppm
ATEmix (inhalation-vapour)	157.1429 mg/l
ATEmix (inhalation-dust/mist)	21.40 mg/l

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
butanone	= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
2-Methoxy-1-methylethyl acetate	= 8532 mg/kg (Rat)	> 5 g/kg (Rabbit)	= 16000 mg/m ³ (Rat) 6 h
1-Methoxy-2-propanol	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards**11.2.1. Endocrine disrupting properties**

Endocrine disrupting properties The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone	-	LC50: 4.74 - 6.33mL/L (96h, <i>Oncorhynchus mykiss</i>) LC50: 6210 - 8120mg/L (96h, <i>Pimephales promelas</i>) LC50: =8300mg/L (96h, <i>Lepomis macrochirus</i>)	-	EC50: 10294 - 17704mg/L (48h, <i>Daphnia magna</i>) EC50: 12600 - 12700mg/L (48h, <i>Daphnia magna</i>)
xylene	EC50: =11mg/L (72h, <i>Pseudokirchneriella subcapitata</i>)	LC50: =13.4mg/L (96h, <i>Pimephales promelas</i>) LC50: 2.661 - 4.093mg/L (96h, <i>Oncorhynchus mykiss</i>) LC50: 13.5 - 17.3mg/L (96h, <i>Oncorhynchus mykiss</i>) LC50: 13.1 - 16.5mg/L (96h, <i>Lepomis macrochirus</i>) LC50: =19mg/L (96h, <i>Lepomis macrochirus</i>) LC50: 7.711 - 9.591mg/L (96h, <i>Lepomis macrochirus</i>) LC50: 23.53 - 29.97mg/L (96h, <i>Pimephales promelas</i>) LC50: =780mg/L (96h, <i>Cyprinus carpio</i>) LC50: >780mg/L (96h, <i>Cyprinus carpio</i>) LC50: 30.26 - 40.75mg/L (96h, <i>Poecilia reticulata</i>)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, <i>Gammarus lacustris</i>)
butanone	-	LC50: 3130 - 3320mg/L (96h, <i>Pimephales promelas</i>)	-	EC50: >520mg/L (48h, <i>Daphnia magna</i>) EC50: =5091mg/L (48h, <i>Daphnia magna</i>) EC50: 4025 - 6440mg/L (48h, <i>Daphnia magna</i>)
2-Methoxy-1-methylethyl acetate	-	LC50: =161mg/L (96h, <i>Pimephales promelas</i>)	-	EC50: >500mg/L (48h, <i>Daphnia magna</i>)
1-Methoxy-2-propanol	-	LC50: =20.8g/L (96h,	-	EC50: =23300mg/L (48h,

	Pimephales promelas)		Daphnia magna)
--	----------------------	--	----------------

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Chemical name	Partition coefficient
Petroleum gases, liquefied	2.8
Acetone	-0.24
xylene	3.15
butanone	0.3
2-Methoxy-1-methylethyl acetate	1.2
1-Methoxy-2-propanol	1

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Petroleum gases, liquefied	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB
xylene	The substance is not PBT / vPvB
butanone	The substance is not PBT / vPvB
2-Methoxy-1-methylethyl acetate	The substance is not PBT / vPvB
1-Methoxy-2-propanol	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	None
EmS-No	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	No information available

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	None

ADR

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	AEROSOLS, FLAMMABLE
14.3 Transport hazard class(es)	2.1
14.4 Packing group	None
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	None
Tunnel restriction code	(D)

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Chemical name	French RG number
Acetone - 67-64-1	RG 84
xylene - 1330-20-7	RG 4bis, RG 84
butanone - 78-93-3	RG 84
2-Methoxy-1-methylethyl acetate - 108-65-6	RG 84
1-Methoxy-2-propanol - 107-98-2	RG 84

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Chemical name	Netherlands - List of Carcinogens	Netherlands - List of Mutagens	Netherlands - List of Reproductive Toxins
xylene	-	-	Development Category 2

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Authorisations and/or restrictions on use:

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Petroleum gases, liquefied - 68476-85-7	Use restricted. See item 28. Use restricted. See item 29. Use restricted. See item 75.	-
Acetone - 67-64-1	Use restricted. See item 75.	-
xylene - 1330-20-7	Use restricted. See item 75.	-
butanone - 78-93-3	Use restricted. See item 75.	-

Persistent Organic Pollutants

Not applicable

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Petroleum gases, liquefied - 68476-85-7	50	200

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status
DSL/NDSL	Contact supplier for inventory compliance status
EINECS/ELINCS	Contact supplier for inventory compliance status
ENCS	Contact supplier for inventory compliance status
IECSC	Contact supplier for inventory compliance status
KECL	Contact supplier for inventory compliance status
PICCS	Contact supplier for inventory compliance status
AIIC	Contact supplier for inventory compliance status
NZIoC	Contact supplier for inventory compliance status

Legend:

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AIIC - Australian Inventory of Industrial Chemicals
NZIoC - New Zealand Inventory of Chemicals

15.2. Chemical safety assessment

Chemical Safety Report

No information available

SECTION 16: Other information**Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

H220 - Extremely flammable gas

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling Maximum limit value

*

Skin designation

+ Sensitisers

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 28/09/2023

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet