



NOTE 1. NO PLATING ON THE SHEARED EDGES OF CONTACT.
 NOTE 2. CRIMP TYPE ARE MARKED AS INDICATED.

TABLE 1

CRIMP TYPE	APPLICABLE WIRE		DIMENSIONS			
	WIRE SIZE	INSULATION OUTER DIA.	A	B	C	D
C 1	AWG#18~22 (0.8mm~0.3mm)	φ 2.3MAX.	28.43	5.81	3.92	2.49
C 2	AWG#22~26 (0.3mm~0.13mm)	φ 1.0~φ 1.7	29.04	6.42	4.53	2.7

1	#20PIN CONTACT	1	COPPER ALLOY	SILVER PLATING	
ITEM	DESCRIPTION	Q'TY	MATERIAL	FINISH	REMARKS
UNLESS OTHERWISE SPECIFIED: T700142		DATE	TITLE		
DIMENSIONS ARE IN MILLIMETERS TOLERANCES ON : (INCHES) FRACTIONS DECIMALS ANGLES		13. Mar. '95	<div style="font-size: 2em; font-weight: bold; opacity: 0.5;">JAE-CONNECTOR.COM</div> <div style="font-size: 1.5em; font-weight: bold; opacity: 0.5;">Reference Only</div>		
		DRAWN			
		S. NANA O			
		CHECKED			
		T. MORITA			
APP'D	(#20PIN CONTACT) (INDIVIDUAL)		MUSASHINO, AKISHIMA-SHI TOKYO, JAPAN		
M. Takagi					
APP'D	SERIES	SCALE	DWG. NO. SJ025420-E		
	JL05	3/1			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[JAE Electronics:](#)

[ST-JL05-20P-C1-100](#) [ST-JL05-20P-C2-100](#)