

## Digital Wireless Stereo Earphones [RZ-B110W]

			RZ-B110W
<b>General</b>	Power Supply	Charging cradle	DC 5V, 500 mA
	Built-in Battery	Earphones	3.7V, Lithium polymer
		Charging cradle	3.7V, Lithium polymer
	Built-in Battery Capacity	Earphones	45 mAh
		Charging cradle	400 mAh
	Operating Time (AAC)	Earphones	Approx. 6.0 hours
		Earphones with Charging cradle	Approx. 26 hours
	Playback Time with Battery (SBC)	Earphones	Approx. 6.0 hours
		Earphones with Charging cradle	Approx. 26 hours
	Quick Charge (15 minutes, AAC)	Earphones	Approx. 70 minutes
	Charging Time (25 °C/77 °F)	Earphones	Approx. 2.5 hours
		Charging cradle	Approx. 2.5 hours
		Earphones with Charging cradle	Approx. 2.5 hours
	Charging temperature range		10 °C to 35 °C (50 °F to 95 °F)
Operating temperature range		0 °C to 40 °C (32 °F to 104 °F)	
Operating humidity range		35 %RH to 80 %RH (no condensation)	
Mass	Earphones (one side only: L and R are the same)	Approx. 4.2 g	
	Charging cradle	Approx. 34 g	
Dimensions (W X H X D)	Earphones (with Earpiece M size)	Approx. 22 mm x 34 mm x 25 mm	
	Charging cradle	Approx. 62 mm x 45 mm x 25 mm	
<b>Bluetooth® section</b>	Bluetooth® system specification		Ver. 5.3
	Wireless equipment classification		Class 2
	Max RF Power (e.i.r.p)		4 dBm
	Frequency band		2402 MHz to 2480 MHz
	Supported profiles		A2DP, AVRCP, HFP
	Supported codec		SBC, AAC
	Operating distance		Up to 10 m (33 ft)
	Wireless Frequency band		20 Hz to 20,000 Hz
<b>Earphones section</b>	Driver unit		10 mm
	Noise Canceling		-
	Microphone		Mono
<b>Accessory section</b>	USB Charging Cord		USB charging cord: Approx. 0.2 m (Input Plug: USB Type-A Shape, Output Plug: USB Type-C Shape)
	Earpieces set		S, M, L each 2pcs (Size M Attached)
<b>Water resistant</b>	Water Resistance		IPX4 Equivalent (Earphones only)

