

Digital Wireless Stereo Earphones [RZ-B110W/RZ-B310W]

		RZ-B310W	
General	Power Supply	Charging cradle	DC 5V, 500 mA
	Built-in Battery	Earphones	3.7V, Lithium polymer
		Charging cradle	3.7V, Lithium polymer
	Built-in Battery Capacity	Earphones	40 mAh
		Charging cradle	330 mAh
	Operating Time (AAC)	Earphones	Approx. 5.0 hours (NC ON) Approx. 6.0 hours (NC OFF)
		Earphones with Charging cradle	Approx. 16.0 hours (NC ON) Approx. 20.0 hours (NC OFF)
	Playback Time with Battery (SBC)	Earphones	Approx. 5.0 hours (NC ON) Approx. 6.0 hours (NC OFF)
		Earphones with Charging cradle	Approx. 16.0 hours (NC ON) Approx. 20.0 hours (NC OFF)
	Quick Charge (15 minutes, AAC)	Earphones	Approx. 60 minutes (NC ON)
	Charging Time (25 °C/77 °F)	Earphones	Approx. 2.5 hours
		Charging cradle	Approx. 2.5 hours
		Earphones with Charging cradle	Approx. 2.5 hours
	Charging temperature range	10 °C to 35 °C (50 °F to 95 °F)	
	Operating temperature range	0 °C to 40 °C (32 °F to 104 °F)	
Operating humidity range	35 %RH to 80 %RH (no condensation)		
Mass	Earphones (one side only: L and R are the same)	Approx. 4.7 g	
	Charging cradle	Approx. 40 g	
Dimensions (W X H X D)	Earphones (with Earpiece M size)	Approx. 22 mm x 33 mm x 25 mm	
	Charging cradle	Approx. 61 mm x 47 mm x 29 mm	
Bluetooth® section	Bluetooth® system specification	Ver. 5.3	
	Wireless equipment classification	Class 2	
	Max RF Power (e.i.r.p)	4 dBm	
	Frequency band	2402 MHz to 2480 MHz	
	Supported profiles	A2DP, AVRCP, HFP	
	Supported codec	SBC, AAC	
	Operating distance	Up to 10 m (33 ft)	
	Wireless Frequency band	20 Hz to 20,000 Hz	
Earphones section	Driver unit	10 mm	
	Noise Cancelling	-30 dB (50-120 Hz)	
	Microphone	Mono	
Accessory section	USB Charging Cord	USB charging cord: Approx. 0.2 m (Input Plug: USB Type-A Shape, Output Plug: USB Type-C Shape)	
	Earpieces set	S, M, L each 2pcs (Size M Attached)	
Water resistant	Water Resistance	IPX4 Equivalent (Earphones only)	

