

Rittal – The System.

Faster – better – everywhere.

Air/water heat exchangers wall-mounted – SK 3214.100

Date : Apr 26, 2021

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Air/water heat exchangers wall-mounted – SK 3214.100

created: 26.04.2021 build on www.rittal.com/uk-en



Product description

Design:	Water-carrying parts, copper/brass (Cu/CuZn)
Description:	For use in harsh environments and temperature ranges up to +70 °C. User-friendly assembly plus flexible water connection options. External mounting or full internal mounting are supported.
Colour:	RAL 7035
Protection category IP to IEC 60 529:	IP 55
Protection category NEMA:	UL Type 1
Supply includes:	Fully wired ready for connection Drilling template Sealing and assembly parts

Product description

Total cooling output:	L 35 W 10 at 200 l/h: 0.6 kW L 35 W 10 at 400 l/h: 0.7 kW
Air throughput (unimpeded air flow):	Internal circuit at 50 Hz: 280 m³/h Internal circuit at 60 Hz: 310 m³/h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 200 mm Height: 500 mm Depth: 100 mm

Temperature control:	Thermostat-controlled magnetic valve
Temperature range:	Operation (environment): +1 °C...+70 °C Setting range: +20 °C...+55 °C Water inlet: +1 °C...+30 °C
Refrigerant/cooling medium:	Cooling medium: Water (see Internet for specifications)
Duty cycle:	100 %
Power consumption P_{el}:	At 50 Hz: 36 W At 60 Hz: 37 W
Rated current max.:	At 50 Hz: 0.17 A At 60 Hz: 0.18 A
Miniature circuit-breaker/fuse:	2 A
Permissible operating pressure (p. max.):	1 bar - 10 bar
Temperature monitoring:	Internal thermostat, with change-over contact, switching load 16 A, setting range +20 °C ... +60 °C (factory setting +35 °C)
Water connections:	½" connector sleeve
eCl@ss 8.0/8.1:	27180712
Packs of:	1 pc(s).
Weight/pack:	7 kg
EAN:	4028177232853
Customs tariff number:	84158300
ETIM 7.0:	EC002515
ETIM 6.0:	EC002515
eCl@ss 8.0/8.1:	27180712
eCl@ss 6.0/6.1:	27180712
Product description:	SK Air/water heat exchanger, wall-mounted, 0.6 kW, 230 V, 1~, 50/60 Hz, Water-carrying parts: copper/brass , WHD: 200 x 500 x 100 mm

Approvals

Approvals:	Approval overview CSA UL + C-UL - FTTA UR + C-UR
-------------------	---

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------
