



KEY-B CONFIGURATION
P/N ATM06-12SB-CAP
INSERT COLOR: BLACK



KEY-C CONFIGURATION
P/N ATM06-12SC-CAP
INSERT COLOR: GREEN



KEY-D CONFIGURATION
P/N ATM06-12SD-CAP
INSERT COLOR: BROWN

REVISIONS					
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1	-	RELEASE	26JUN15	JAH	
A2	-	REVISED COLOR AND IP RATING	20NOV2020	JAH	DH

NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL: THERMOPLASTIC, HOUSING COLOR: GREY
INSERT COLOR: PER KEY CONFIGURATION
- RoHS COMPLIANT
- MOISTURE RESISTANCE: IP68 (1M OF WATER FOR
A PERIOD OF 24 HOURS , MATED CONDITION)
- TEMPERATURE RANGE: -55C~125C
- USE WITH CONNECTORS ATM06-12SX*
(X = A,B,C,D KEYS; * = MODIFICATIONS AND/OR COLORS)
- ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

SEE KEY OPTIONS		DESCRIPTION		ITEM
QUANTITY	PART NUMBER	MATERIALS LIST		
UNLESS OTHERWISE SPECIFIED: 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.15 3 PL DEC ±0.08 Fractions ±1/64 Angles ±1°		SIGNATURES	DATE	<p style="text-align: center;">Amphenol</p> <p style="text-align: center;">Sine Systems - www.amphenol-sine.com 44724 Morley Drive Clinton Township, MI 48036</p>
DRAWN: J.HEAD		23JUN2015	<p style="text-align: center;">PROTECTIVE CAP, 12 POSITION, ATM-SERIES</p>	
CHECKED:				
ENGINEER:				
APPROVAL:		CUSTOMER:		<p>SEE TYPE: B C- DWG NO: ATM06-12SX-CAP REVISION: A2</p> <p>SCALE: NONE SHEET 1 OF 1</p>
MATERIAL SPECIFICATIONS:		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		
PROCESS SPECIFICATIONS:				
NEXT ASSY:				

TITLE: PROTECTIVE CAP, 12 POSITION, ATM-SERIES
DWG NO: ATM06-12SX-CAP
REV: A2
SH: 1
OF: 1