Product Search Data Sheet




NCP18XV103E03RB

In Production RoHS REACH Recommended

Appearance & Shape





(in mm)

Applications

Limited Usage	Consumer Grade
Other Usage	1. Temperature compensation for transistor, IC and crystal oscillator in mobile communications 2. Temperature sensor for rechargeable batteries 3. Temperature compensation of LCD 4. Temperature compensation in general use of electric circuits

Packaging Information

Packaging	Specifications	Minimum Order Quantity	
RB	180mm Paper Tape	4000	



- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible

5. Same B-Constant in the same resistance in the three sizes (0805 size / 0603 size / 0402 size)

- Easy to use smaller size in the circuits
- 6. Lead is not contained in the product.
- 7. NCP series are recognized by UL/cUL (UL1434, File No.E137188).

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



1 of 3

Note: This datasheet may be out of date Please download the latest datasheet of NCP18XV103E03RB from the official website of Murata Manufacturing Co., Ltd. n/en-SG/products/productdetail?partno=NCP18XV103E03RB



Product Search Data Sheet

NCP18XV103E03RB

Note: This datasheet may be out of date. Please download the latest datasheet of NCP18XV103E03RB from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-SG/products/productdetail?partno=NCP18XV103E03RB

Specifications

Resistance (25°C)	10kΩ
Resistance Value Tolerance (at 25°C)	±3%
B-Constant (25/50°C)	3900K
B-Constant (25/50°C) Tolerance	±3%
B-Constant(25/80°C)(Reference Value)	3930K
B-Constant(25/85°C)(Reference Value)	3934K
B-Constant(25/100°C)(Reference Value)	3944K
Max. Voltage	5V
Maximum Operating Current (25°C)	0.1mA
Typical Dissipation Constant (25°C)	1mW/°C
Operating Temperature Range	-40°C to 125°C
Size Code (in mm)	1.6x0.8mm
Size Code (in inch)	0.6x0.3inch
Shape	SMD
Mass	0.0047g

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Attention


Product Search Data Sheet




NCP18XV103E03RB

Note: This datasheet may be out of date Please download the latest datasheet of NCP18XV103E03RB from the official website of Murata Manufacturing Co., Ltd. http://www m/en-SG/products/productdetail?partno=NCP18XV103E03RB

Product Data





Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



3 of 3