



1) Einlotstifte passend für Lochungen
 $\phi 1 \pm 0,1$ nach IEC 60326-3
Solder pins for PCB connections
 $\phi 1 \pm 0,1$ as per IEC 60326-3
 A souder pour des trous de $\phi 1 \pm 0,1$
 selon IEC 60326-3

| | | | | | | | | | | | | | |
|---|-------------|-----------------------|-----|-------|-----------|------|-------------------------------|-----------|----|--|--------------------------------------|---|----------------------------|
| A | 09195507322 | 3 | 4,5 | | | | | | | | All Dim. in mm Orig. Size DIN A 4 | SEK 19 Male connector 50 poles, low profile, high temperature with straight pins | Maßstab/ Scale 1.5:1 |
| | 09195506322 | 2 | 4,5 | | | | Detail. | 25-APR-02 | CV | | | | |
| | 09195505322 | 0.76 μm Au | 4,5 | | | | Insp. | | | | | | |
| | 09195507324 | 3 | 2,9 | | | | Stand. | | | | | | |
| | 09195506324 | 2 | 2,9 | | | | | | | | | | |
| | 09195505324 | 0.76 μm Au | 2,9 | 29778 | 25-APR-02 | CV | | | | | | | |
| | Part-No. | performance level | 0 | Mod. | Dat. | Name | HARTING EURL F-95972 Paris | | | | TB 0919550x32x Sub. | Blatt/ Page 1 / 2 | |