

# HUBER+SUHNER® DATA SHEET

## Coaxial Panel Connector: 22\_MMBX-50-0-1/111\_N

Rev.: G



### Description

Straight bulkhead receptacle jack

Interface standards  
SUHNER-MMBX



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 12.4 GHz

#### Mechanical Data

Chassis torque 2 Nm  
Weight 0.0014 kg

#### Environmental Data

Operating Temperature -55 °C to 155 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	LCP (Liquid crystal polymer)

##### Surface Plating

Gold Plating (Nickel underplated)  
SUCOPRO Plating  
SUCOPRO Plating

#### Related Documents

Outline drawing DOU-00010456  
Catalogue drawing DCA-00010458

#### Ordering Information

Single package 22\_MMBX-50-0-1/111\_NE

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**