



PIN OUT

DB9F	DB9F
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
shell	shell

NOTE:

1. Using 9C+1 WIRE.
2. L=1.8M,3M

序号/Rev.No.	更改记录 /Revision note	签名 /Signature	日期 /date
------------	---------------------	---------------	----------

设计 /Designed by	绘图 /Drawing by	审核 /Checked by	批准 /Approvotry																
 新莱亚电子科技 XINLANTA ELECTRONIC CO.,LTD		图名 /Title	文件编号 /File No.																
		DB9F/9F	页序 /Sheet																
备注 /Remark		XY0016	未注公差 General Tolerance																
			<table border="1"> <tr> <td>X</td> <td>± 0.2</td> <td>X'</td> <td>± 2</td> </tr> <tr> <td>.X</td> <td>± 0.1</td> <td>.X'</td> <td>± 1</td> </tr> <tr> <td>.XX</td> <td>± 0.05</td> <td>.XX'</td> <td>± 0.5</td> </tr> <tr> <td>.XXX</td> <td>± 0.01</td> <td></td> <td></td> </tr> </table>	X	± 0.2	X'	± 2	.X	± 0.1	.X'	± 1	.XX	± 0.05	.XX'	± 0.5	.XXX	± 0.01		
X	± 0.2	X'	± 2																
.X	± 0.1	.X'	± 1																
.XX	± 0.05	.XX'	± 0.5																
.XXX	± 0.01																		
			单位 /Units: mm																