

REAL TIME CLOCK MODULE (I²C-Bus)

Built-in 32.768 kHz-DTCXO

RX 8804CE

- Built in frequency adjusted 32.768 kHz crystal unit and DTCXO.
- Interface Type : I²C-Bus interface (400kHz)
- Interface voltage range : 1.6 V to 5.5 V
- Temp. compensated voltage range : 1.5 V to 5.5 V
- Timekeeping voltage range : 1.5 V to 5.5 V
- Selectable clock output (32.768 kHz, 1024 Hz, 1 Hz)
- The various functions full calendar, alarm, timer, event detection.
- The time-stamp synchronizing to the event detection of EVIN-pin.
- The SOUT-pin outputs that selected flag bit value.
- Applications : handy equipment. an outdoor unit. an industrial machine.

*The I²C-BUS is a trademark of NXP Semiconductors.



Product Number (Please contact us)
RX8804CE : X1B000371xxx00




RX8804CE
(3.2 × 2.5 × 1.0 mm)

Actual size

RX8804CE



Block diagram



Overview

• Stability

- XA
± 3.4 × 10⁻⁶ / -40 °C to +85 °C
± 8.0 × 10⁻⁶ / +85 °C to +105 °C
- XB
± 5.0 × 10⁻⁶ / -40 °C to +85 °C
± 8.0 × 10⁻⁶ / +85 °C to +105 °C

• 32.768 kHz frequency output function

- FOUT pin output (C-MOS output), CL=30 pF
- Output selectable: 32.768 kHz, 1024 Hz, 1 Hz

• Event detection function

- When trigger input to EVIN-pin or specified by program, time and date is recorded. The EVIN-pin with pull-up resistor that is releasable.

• Timer function

- Timer source clock are 1min., 1sec., 64Hz, 4096Hz.
- 24-bit-presetable counter (244us to about 32years.)

• Alarm function

- Alarm function can be set to day of week, day, hour, and minute.

• Internal state output function


- SOUT pin output (C-MOS output),
- It outputs selected flag-bit value or specified value(H or L).

Pin Function

Signal Name	I / O	Function
SOUT	Output	Internal state output pin.
SCL	Input	Serial clock input pin.
FOUT	Output	The pin outputs the reference clock signal. (CMOS output)
EVIN	Input	Event input pin
V _{DD}	-	Connected to a positive power supply
FOE	Input	The input pin for the FOUT output control.
/ INT	Output	Interrupt output (N-ch. open drain).
GND	-	Connected to a ground
T2	-	Use only for testing in the factory. (Do not connect externally.)
SDA	I/O	Data input and output pin.

Terminal connection / External dimensions

(Unit:mm)



Specifications (characteristics)


* Refer to application manual for details.

■ Electrical Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
Operating voltage	V _{DD}	Interface voltage	1.6	3.0	5.5	V
Temp. compensated Voltage	V _{TEM}	Temp. compensated voltage	1.5	3.0	5.5	V
Clock supply voltage	V _{CLK}	Internal clock	1.5	3.0	5.5	V
Operating temperature	T _{OPR}	No condensation	-40	+25	+105	°C
Stability	Δf / f	XA	T _a = -40 °C ~ +85 °C	±3.4 *1		× 10 ⁻⁶
			T _a = +85 °C ~ +105 °C	±8.0 *2		
		XB	T _a = -40 °C ~ +85 °C	±5.0 *3		
			T _a = +85 °C ~ +105 °C	±8.0 *2		
Current consumption (1)	I _{DD1}	fSCL=0Hz, /INT=V _{DD} , FOE =GND, FOUT: OFF	-	0.4	1.6	μA
Current consumption (2)	I _{DD2}	Temp. Compensation interval 2.0 s.	-	0.35	1.5	

*1) Equivalent to ±9 seconds of month deviation. *2) Equivalent to ±21 seconds of month deviation. *3) Equivalent to ±13 seconds of month deviation.

■ 32.768 kHz-DTCXO Frequency temperature characteristics (Example)



PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.





WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs,

Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired ISO/TS 16949 certification that is requested strongly by major automotive manufacturers as standard.

ISO/TS16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

► Explanation of the mark that are using it for the catalog

	► Pb free.
	► Complies with EU RoHS directive. *About the products without the Pb-free mark. Contains Pb in products exempted by EU RoHS directive. (Contains Pb in sealing glass, high melting temperature type solder or other.)
	► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
	► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc).

Notice

- This material is subject to change without notice.
- Any part of this material may not be reproduced or duplicated in any form or any means without the written permission of Seiko Epson.
- The information about applied data, circuitry, software, usage, etc. written in this material is intended for reference only. Seiko Epson does not assume any liability for the occurrence of customer damage or infringing on any patent or copyright of a third party. This material does not authorize the licensing for any patent or intellectual copyrights.
- When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations.
- You are requested not to use the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes. You are also requested that you would not make the products available to any third party who may use the products for such prohibited purposes.
- These products are intended for general use in electronic equipment. When using them in specific applications that require extremely high reliability, such as the applications stated below, you must obtain permission from Seiko Epson in advance.
/ Space equipment (artificial satellites, rockets, etc.) / Transportation vehicles and related (automobiles, aircraft, trains, vessels, etc.) / Medical instruments to sustain life / Submarine transmitters / Power stations and related / Fire work equipment and security equipment / traffic control equipment / and others requiring equivalent reliability.
- All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective.