



Intel® Xeon® E-2276ML Processor

12M Cache, 2.00 GHz

Specifications

Ordering and Compliance

Ordering and spec information

Intel® Xeon® E-2276ML Processor (12M Cache, 2.00 GHz) FC-BGA14F, Tray

Spec Code	SRFEG
Ordering Code	CL8068404165100
Shipping Media	TRAY
Stepping	U0
Recommended Customer Price	\$450.00

Trade compliance information

ECCN	5A992C
CCATS	G077159
US HTS	8542310001

All information provided is subject to change at any time, without notice. Intel may make changes to manufacturing life cycle, specifications, and product descriptions at any time, without notice. The information herein is provided "as-is" and Intel does not make any representations or warranties whatsoever regarding accuracy of the information, nor on the product features, availability, functionality, or compatibility of the products listed. Please contact system vendor for more information on specific products or systems.

Intel classifications are for informational purposes only and consist of Export Control Classification Numbers (ECCN) and Harmonized Tariff Schedule (HTS) numbers. Any use made of Intel classifications are without recourse to Intel and shall not be construed as a representation or warranty regarding the proper ECCN or HTS. Your company as an importer and/or exporter is responsible for determining the correct classification of your transaction.

Refer to Datasheet for formal definitions of product properties and features.

‡ This feature may not be available on all computing systems. Please check with the system vendor to determine if your system delivers this feature, or reference the system specifications (motherboard, processor, chipset, power supply, HDD, graphics controller, memory, BIOS, drivers, virtual machine monitor-VMM, platform software, and/or operating system) for feature compatibility. Functionality, performance, and other benefits of this feature may vary depending on system configuration.

Max Turbo Frequency refers to the maximum single-core processor frequency that can be achieved with Intel® Turbo Boost Technology. See www.intel.com/technology/turboboost/ for more information.

System and Maximum TDP is based on worst case scenarios. Actual TDP may be lower if not all I/Os for chipsets are used.

"Announced" SKUs are not yet available. Please refer to the Launch Date for market availability.

Processors that support 64-bit computing on Intel® architecture require an Intel 64 architecture-enabled BIOS.

Check <http://ipt.intel.com/> for systems that support Intel® Identity Protection Technology (Intel® IPT).

See <http://www.intel.com/content/www/us/en/architecture-and-technology/hyper-threading/hyper-threading-technology.html?wapkw=hyper+threading>

for more information including details on which processors support Intel® HT Technology.

Some products can support AES New Instructions with a Processor Configuration update, in particular, i7-2630QM/i7-2635QM, i7-2670QM/i7-2675QM, i5-2430M/i5-2435M, i5-2410M/i5-2415M. Please contact OEM for the BIOS that includes the latest Processor configuration update.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See <http://www.intel.com/content/www/us/en/processors/processor-numbers.html> for details.

Company Information

Our Commitment

Communities


Investor Relations

Contact Us

Newsroom

Jobs



USA (English) 



© Intel Corporation

[Terms of Use](#)

*Trademarks

[Privacy](#)

[Cookies](#)

[Supply Chain Transparency](#)

[Site Map](#)