

cannon

Interconnect Solutions for e-mobility

IEC, SAE and GB/T



ITT

We Connect

The future of e-mobility

Drawing upon 100 years of interconnect excellence and nearly a decade of innovation in the Electric Vehicle industry, ITT represents a committed partner to today's e-mobility industry, bringing connection solutions to the market that are truly Engineered for Life.

Global solutions for the EV industry

The ITT difference

- Proven application expertise
- Global capabilities & local support
- Unrivalled customization expertise
- A committed innovator & business partner

About ITT

ITT is a diversified leading manufacturer of highly engineered critical components and customized technology solutions for the energy, transportation and industrial markets. Building on its heritage of innovation, ITT partners with its customers to deliver enduring solutions to the key industries that underpin our modern way of life. Founded in 1920, ITT is headquartered in White Plains, N.Y., with employees in more than 35 countries and sales in a total of approximately 125 countries. For more information visit www.itt.com



IEC, SAE and GB/T e-mobility Interconnect Solutions

ITT's class leading UL and CE certified connectors, plugs, inlets, outlets and accessories offer recognized, trusted and proven charging solutions for today's e-mobility markets. Built in accordance with all key regional standards - IEC 62196 for Europe, SAE J1772 for the Americas and Japan and GB/T 20234 for China they provide a truly global portfolio.

ITT offers a fully comprehensive range of AC charging options— with an industry leading amperage range from 10A to 80A, single and triple phase variants, low contact resistance and a minimum of 10k mating cycles. In addition to off the shelf solutions our EV offering is fully customizable to meet specific requirements and we are able to offer variants on colors, harnesses and terminals.

By using common coupler connector/plug elements such as an ergonomically designed handle, robust contact system, innovative wire positioners and strain relief system ITT is able to serve global industry players with a consistent, recognizable look and feel to support their own product, user and brand experience.



Key features

- Cable options certified and approved to regional requirements
- Sealing to meet and exceed specifications
- Up to 80A AC Charging option
- Low contact resistance
- Minimum 10k mating cycles
- Connector and plug strain relief provides protection from cable oversteering

Applications

- Home EV Charging Units
- Public Charging Stations
- Roadside Assistance Trucks
- Fleet Trucks
- EV Mass Transit Vehicles
- Electric Watercraft
- Passenger Vehicles
- Electric Motorcycles
- Electric Agriculture Vehicles

An e-mobility leader

- A truly global product portfolio
- Extensive customization options
- A track record of EV innovation
- A pioneer in DC fast charging technology

The Gen 2+ Contact System

ITT's new Gen2+ contact system utilizes a state of the art canted coiled spring design that delivers extended lifetime usage and minimizes mechanical stress, miss alignment and power loss.

Dimensions shown in mm
Specifications and dimensions subject to change

www.ittcannon.com





IEC electric vehicle charging solutions



ITT’s IEC e-mobility solutions are built in accordance with IEC 62196-1 and 62196-2 standards for single and three phase charging systems.

IEC performance data	
Temperature Range	-30°C to +50°C
Durability	10,000 mating cycles min
Sealing Requirements	IP 44 min per IEC 61851-1 and tested in accordance with IEC 60525
Certifications Connector	CE, ETL, IEC 62196-1 and IEC 62196-2
Certifications Cable	DIN EN 50620

Key Features

- Drain holes at the bottom of the coupler connector/plug – eliminates latch freezing and includes protective shield from small diameter metal penetration to the wiring.
- Textured coupler connector/plug handle – provides enhanced grip while in use.
- Optional mating face protection – lanyard dust caps options for coupler connector/plug and spring cap options for inlets provide additional protection when connectors are not in use.

ECIER Outlet



How to order

ECIER 20 2 1 -017 S 2 A 1 A 0 A 0 -001

Connector Series & Style

Current Rating (Cable size)

Cable Rating

Powering System (Connector Voltage Rating)

Cable Length (3 Digits)

Sealing Method

Compression Limiter / Metal Inserts in Flange Holes

Dust Cap / Spring Cap

Drain Spout

Locking Device

Rubber Boot

Mounting Hole Pattern

Flange Gasket

Modification Code - If Applicable (3 digits)

Explanation

Connector Series & style

ECIER - EVC IEC 62196 Type 2 Connector EVSE
Rear mount inlet

Current Rating (Cable size)

20A, 32A, 63A

Cable Rating

2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (250VAC)

3 - Three phase (480VAC)

Cable Length (3 Digits)

XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method

S - Sealed

Compression Limiter / Metal Inserts in Flange Holes

0 - Without compression limiter/inserts

1 - Compression limiter (front mounting)

2 - Compression limiter with threaded inserts
M4 (front mounting)

Dust Cap / Spring Cap

A - No dust cap supplied

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

K - With mounting ring thin (to be used with mounting
hole pattern "B" only) (metal inserts M4)

L - With mounting ring (to be used with mounting
hole pattern "B" only) (metal inserts M4)

M - Dust cap PA lanyard, ring terminal (125mm)

N - Dust cap PA lanyard (125mm)

Drain Spout

0 - Without drain spout

1 - With drain spout, without tube

2 - With drain spout with tube; 1m long

3 - With drain spout with tube, 2m long

Locking Device

A - No locking device

B - Motorized switch assembly
(No male connector supplied for locking).

C - Motorized switch assembly including connector
& 300mm cable

D - Motorized switch assembly including connector
& 300mm cable & socket contacts on single wires

E - Solenoid 12VDC assembly (cable length 250mm)

F - Solenoid 24VDC assembly (cable length 250mm)

G - Solenoid 12VDC assembly (same as cable length)

H - Solenoid 24VDC assembly (same as cable length)

Rubber Boot

0 - No rubber boot supplied

Mounting Hole Pattern

B - 58x61mm

C - 52x52mm

Flange Gasket

0 - No flange gasket supplied.

1 - With flange gasket

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification


Dimensions shown in mm

Specifications and dimensions subject to change

www.ittcannon.com



ECCE Plug



How to order

	ECCE	20	2	1	-017	S	0	A	-ECCV	0	A	-001
Connector Series & Style												
Current Rating (Cable size)												
Cable Rating												
Powering System (Connector Voltage Rating)												
Cable Length (3 Digits)												
Sealing Method												
Direction of Cable Strain Relief												
Dust Cap												
Modification Code (4 Letters)												
Direction of Cable Outlet												
Dust Cap												
Modification Code - If Applicable (3 digits)												

Explanation

Connector Series & style*

ECCE - EVC IEC 62196 Type 2 mode 3 connection cable EVSE coupler to vehicle coupler

Current Rating (Cable size)

20A, 32A, 63A

Cable Rating

2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (250VAC)

3 - Three phase (480VAC)

Cable Length (3 Digits)

XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method

S - Sealed

Direction of strain relief ECCE

0 - Straight cable strain relief

1 - Angled cable strain relief (90° Downwards) (not for 63A)

Dust Cap

A - No dust cap supplied

B - Dust cap rubber lanyard (187mm)

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

F - Dust cap PA lanyard (125mm)

Modification Code (4 Letters)

ECCV - Connection cable IEC type 2 connector on 2-end

GBCV - Connection cable GBCV connector on 2-end

EJCV - Connection cable IEC type 1 connector on 2-end (same connector as J2CE) only 1 phase existing

Direction of strain relief of second connector

0 - Straight cable strain relief

1 - Angled cable strain relief (90° Downwards) (not for 63A)

Dust Cap

A - No dust cap supplied

B - Dust cap rubber lanyard (only for GBCV at second end)

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

F - Dust cap PA lanyard (125mm)

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification

179 - Handles in black color


* Default handle color is white



Dimensions shown in mm
Specifications and dimensions subject to change

www.ittcannon.com

ECCV Connector



How to order

	ECCV	20	2	1	-017	S	0	A	-001
Connector Series & Style									
Current Rating (Cable size)									
Cable Rating									
Powering System (Connector Voltage Rating)									
Cable Length (3 Digits)									
Sealing Method									
Direction of Cable Strain Relief									
Dust Cap									
Modification Code - If Applicable (3 digits)									

Explanation

Connector Series & style*

ECCV - EVC IEC 62196 Type 2 Connector vehicle coupler

Current Rating (Cable size)

20A, 32A, 63A

Cable Rating

2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (250VAC)
3 - Three phase (480VAC)

Cable Length (3 Digits)

XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method

S - Sealed

Direction of Cable Strain Relief

0 - Straight cable strain relief
1 - Angled cable strain relief (90° downwards, except for 63A)

Dust Cap


A - No dust cap supplied
C - Dust cap stainless steel lanyard (155mm).
D - Dust cap stainless steel lanyard (125mm)
E - Dust cap PA lanyard (155mm)
F - Dust cap PA lanyard (125mm)

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification
179 - Handles in black color

* Default handle color is white

ECIV Inlet



How to order

	ECIV	20	2	1	-017	S	1	A	1	A	0	A	0	-001
Connector Series & Style														
Current Rating (Cable size)														
Cable Rating														
Powering System (Connector Voltage Rating)														
Cable Length (3 Digits)														
Sealing Method														
Compression Limiter / Metal Inserts in Flange Holes														
Dust Cap / Spring Cap														
Drain Spout														
Locking Device														
Rubber Boot														
Mounting Hole Pattern														
Flange Gasket														
Modification Code - If Applicable (3 digits)														

Explanation

- Connector Series & style**
ECIV - EVC IEC 62196 Type 2 Connector vehicle inlet
- Current Rating (Cable size)**
20A, 32A, 63A
- Cable Rating**
2 - Level 2
- Powering System (Connector Voltage Rating)**
1 - Single phase (250VAC)
3 - Three phase (480VAC)
- Cable Length (3 Digits)**
XXX - Length in 0.1m*XXX (017 = 1.7m)
- Sealing Method**
S - Sealed
- Compression Limiter / Metal Inserts in Flange Holes**
0 - Without compression limiter/inserts
1 - Compression limiter (front mounting)
2 - Compression limiter with threaded inserts M4 (front mounting)
3 - Compression limiter with threaded inserts M5 (front mounting)

- Dust Cap / Spring Cap**
A - No dust cap supplied
C - Dust cap stainless steel lanyard (155mm)
D - Dust cap stainless steel lanyard (125mm)
E - Dust cap PA lanyard (155mm)
G - With spring cap (Opening to left)
H - With spring cap (Opening to the right)
M - Dust Cap PA Lanyard, ring terminal (125mm)
N - Dust cap PA lanyard (125mm)
- Drain Spout**
0 - Without drain spout.
1 - With drain spout, without tube
2 - With drain spout with tube; 1m long
3 - With drain spout with tube, 2m long
- Locking Device**
A - No locking device
B - Motorized switch assembly (No male connector supplied for locking device)
C - Motorized switch assembly including connector and 300mm cable
D - Motorized switch assembly including connector and 300mm cable & socket contacts on single wires


- Rubber Boot**
0 - No rubber boot supplied
- Mounting Hole Pattern**
A - Standard pattern
- Flange Gasket**
0 - No flange gasket supplied
1 - Flange gasket
- Modification Code - If Applicable (3 digits)**
001 to 999 - For customer specific modification



Dimensions shown in mm
Specifications and dimensions subject to change

www.ittcannon.com

EJCV Connector



How to order



	EJCV	20	2	1	-017	S	0	A	-001
Connector Series & Style									
Current Rating (Cable size)									
Cable Rating									
Powering System (Connector Voltage Rating)									
Cable Length (3 Digits)									
Sealing Method									
Direction of Cable Strain Relief									
Dust Cap									
Modification Code - If Applicable (3 digits)									

Explanation

Connector Series & style* EJCV - EVC IEC 62196 Type 1 Connector vehicle coupler	Cable Length (3 Digits) XXX - Length in 0.1m*XXX (017 = 1.7m)	Dust Cap A - No dust cap supplied C - Dust cap stainless steel lanyard (155mm) D - Dust cap stainless steel lanyard (125mm) E - Dust cap PA lanyard (155mm) F - Dust cap PA lanyard (125mm)
Current Rating (Cable size) 20A, 32A	Sealing Method S - Sealed	Modification Code - If Applicable (3 digits) 001 to 999 - For customer specific modification 179 - Handles in black color
Cable Rating 2 - Level 2	Direction of Cable Strain Relief 0 - Straight cable strain relief	
Powering System (Connector Voltage Rating) 1 - Single phase (250VAC)		

* Default handle color is white

EJIV Inlet



How to order

EJIV	20	2	1	-017	S	0	A	0	A	0	A	0	-001
------	----	---	---	------	---	---	---	---	---	---	---	---	------

Connector Series & Style													
Current Rating (Cable size)													
Cable Rating													
Powering System (Connector Voltage Rating)													
Cable Length (3 Digits)													
Sealing Method													
Compression Limiter / Metal Inserts in Flange Holes													
Dust Cap / Spring Cap													
Drain Spout													
Locking Device													
Rubber Boot													
Mounting Hole Pattern													
Flange Gasket													
Modification Code - If Applicable (3 digits)													

Explanation

Connector Series & style
EJIV - EVC IEC 62196 Type 1 Connector vehicle inlet

Current Rating (Cable size)
20A, 32A

Cable Rating
2 - Level 2

Powering System (Connector Voltage Rating)
1 - Single phase (250VAC)

Cable Length (3 Digits)
XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method
S - Sealed

Compression Limiter / Metal Inserts in Flange Holes
0 - Without compression limiter/inserts
1 - Compression limiter (front mounting)
3 - Compression limiter with threaded inserts M5 (front mounting)

Dust Cap / Spring Cap
A - No dust cap supplied
G With spring cap (Opening to left)
H - With spring cap (Opening to right)

Drain Spout
0 - Without drain spout

Locking Device
A - No locking device

Rubber Boot
0 - No rubber boot supplied

Mounting Hole Pattern
A - Standard pattern

Flange Gasket
0 - No flange gasket supplied
1 - Flange gasket

Modification Code - If Applicable (3 digits)
001 to 999 - For customer specific modification



Dimensions shown in mm
Specifications and dimensions subject to change

SAE J1772 electric vehicle charging solutions



ITT's SAE J1772 e-mobility solutions are built in accordance with SAE J1772 standard for AC Level 1 and Level 2 charging systems.

J1772 performance data	
Temperature Range	-30°C to +50°C
Durability	10,000 mating cycles min
Sealing Requirements	Meets UL50, Type 3R/3S
Certifications Connector	UL File E330790, PSE-JET on request
Certifications Cable	UL62, JET on request

Key Features

- Drain holes at the bottom of the coupler connector/plug – eliminates latch freezing and includes protective shield from small diameter metal penetration to the wiring.
- Textured coupler connector/plug handle – provides enhanced grip while in use.
- Optional mating face protection – lanyard dust caps options for coupler connector/plug and spring cap options for inlets provide additional protection when connectors are not in use.

J2CE Connector



How to order

J2CE	16	1	1	-17	S	0	A	-001
------	----	---	---	-----	---	---	---	------

Connector Series & Style

Current Rating (Cable size)

Cable Rating

Powering System (Connector Voltage Rating)

Cable Length (2 Digits)

Sealing Method

Direction of Cable Strain Relief

Dust Cap

Modification Code - If Applicable (3 digits)

Explanation

Connector Series & style*

J2CE - EVC SAE-J1772 Connector vehicle coupler

Current Rating (Cable size)

16 - 16A (level 1 only)

20 - 20A

30 - 30A (level 2 only)

32 - 32A (level 2 only)

40 - 40A (level 2 only)

48 - 48A (level 2 only)

75 - 80A (level 2 & canted coil spring contacting only)

Cable Rating

1 - Level 1

2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (120VAC for level 1, 240VAC for level 2)

Cable Length (2 digits)

XX - Length in ft. (17 = 17ft.)

Power Contact Type

L - Hyperboloid lamella contacting

S - Canted coil spring contacting

Direction of Cable Strain Relief

0 - Straight cable strain relief

Dust Cap

A - No dust cap supplied

C - Dust cap stainless steel lanyard (6.1in)

D - Dust cap stainless steel lanyard (4.9in)

E - Dust cap PA lanyard (6.1in)

F - Dust cap PA lanyard (4.9in)

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification

179 - Handles in black color

273 - Cold temperature (flexible) cable (only for current ratings 30A-80A)

276 - Handles in black color + cold temperature (flexible) cable (only for current ratings 30A-80A)

* Default handle color is white


Dimensions shown in mm

Specifications and dimensions subject to change

www.ittcannon.com



J2IV Inlet



How to order

Connector Series & Style
Current Rating (Cable size)
Cable Rating
Powering System (Connector Voltage Rating)
Cable Length (2 Digits)
Sealing Method
Compression Limiter / Metal Inserts in Flange Holes
Dust Cap / Spring Cap
Drain Spout
Locking Device
Rubber Boot
Mounting Hole Pattern
Flange Gasket
Modification Code - If Applicable (3 digits)

J2IV 20 2 1 -17 S 1 A 0 A 0 A 0 -001

Explanation

Connector Series & style

J2IV - EVC SAE-J1772 Connector vehicle inlet

Current Rating (Cable size)

20 - 20A
40 - 40A (level 2 only)
75 - 75A (level 2 only)
80 - 80A (level 2 only)

Cable Rating

1 - Level 1
2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (120V AC for level 1, 240VAC for levels 2)

Cable Length (2 Digits)

XX - Length in ft. (17 = 17ft)

Sealing Method

S - Sealed

Compression Limiter / Metal Inserts in Flange Holes

0 - Without compression limiter/inserts
1 - Compression limiter (front mounting)
3 - Compression limiter with threaded inserts M5 (front mounting)

Dust Cap / Spring Cap

A - No dust cap supplied.
G - With spring cap (Opening to left)
H - With spring cap (Opening to right)

Drain Spout

0 - Without drain spout

Locking Device

A - No locking device

Rubber Boot

0 - No rubber boot supplied

Mounting Hole Pattern

A - Standard pattern

Flange Gasket

0 - No flange gasket supplied
1 - Flange gasket

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification



Dimensions shown in mm
Specifications and dimensions subject to change

www.ittcannon.com



GB/T electric vehicle charging solutions


ITT's GB e-mobility solutions are built in accordance with GB-T 20234 standards for charging systems.

GB performance data	
Temperature Range	-30°C to +50°C
Durability	10,000 mating cycles min
Sealing Requirements	IP54/IP55
Certifications Connector	CQC 13029087619
Certifications Cable	CQC 1103 or 1104

Key Features

- Drain holes at the bottom of the coupler connector/plug – eliminates latch freezing and includes protective shield from small diameter metal penetration to the wiring.
- Textured coupler connector/plug handle – provides enhanced grip while in use.
- Optional mating face protection – lanyard dust caps options for coupler connector/plug and spring cap options for inlets provide additional protection when connectors are not in use.

GBIE Outlet



How to order

GBIE 16 2 1 -017 S 0 A 1 A 0 A 0 -001

Connector Series & style

Current Rating (Cable size)

Cable Rating

Powering System (Connector Voltage Rating)

Cable Length (3 Digits)

Sealing Method

Compression Limiter / Metal Inserts in Flange Holes

Dust Cap / Spring Cap

Drain Spout

Locking Device

Rubber Boot

Mounting Hole Pattern

Flange Gasket

Modification Code - If Applicable (3 digits)

Explanation

Connector Series & style

GBIE - EVC GB/T 20234 Connector EVSE inlet

Current Rating (Cable size)

10 - 10A (1 phase only)

16 - 16A

32 - 32A

Cable Rating

2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (250VAC)

3 - Three phase (440VAC)

Cable Length (3 Digits)

XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method

S - Sealed

Compression Limiter / Metal Inserts in Flange Holes

0 - Without compression limiter/inserts

1 - Compression limiter (front mounting)

3 - Compression limiter with threaded inserts M5 (front mounting)

Dust Cap / Spring Cap

A - No dust cap supplied

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

F - Dust cap without lanyard, Sealing on OD

M - Dust Cap PA Lanyard, ring terminal (125mm)

N - Dust cap PA lanyard (125mm)

Drain Spout

0 - Without drain spout

1 - With drain spout without tube

2 - With drain spout with tube; 1m long

3 - With drain spout with tube, 2m long

Locking Device

A - No locking device

B - Motorized switch assembly (No male connector supplied for locking device).

C - Motorized switch assembly including connector & 300mm cable

D - Motorized switch assembly including connector & 300mm cable & socket contacts on single wires

E - Solenoid 12VDC assembly (cable length 250mm)

F - Solenoid 24VDC assembly (cable length 250mm)

G - Solenoid 12VDC assembly (same as cable length)

H - Solenoid 24VDC assembly (same as cable length)

Rubber Boot

0 - No rubber boot supplied

Mounting Hole Pattern

A - Standard pattern

Flange Gasket




0 - No flange gasket supplied

1 - Flange gasket

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification

GBCE Plug



How to order

GBCE 16 2 1 -017 S 0 A -ECCV 0 A -001

Connector Series & Style

Current Rating (Cable size)

Cable Rating

Powering System (Connector Voltage Rating)

Cable Length (3 Digits)

Sealing Method

Direction of Cable Strain Relief

Dust Cap

Modification Code for mode 3 combination (4 Letters)

Direction of Cable Strain Relief

Dust Cap

Modification Code - If Applicable (3 digits)

Explanation

Connector Series & style*

GBCE - EVC GB/T 20234 MODE 3 connection cable
EVSE coupler to vehicle coupler

Current Rating (Cable size)

10 - 10A (1 phase only)

16 - 16A

32 - 32A

Cable Rating

2 - Level 2

Power System (Connector Voltage Rating)

1 - Single phase (250VAC)

3 - Three phase (440VAC)

Cable Length (3 Digits)

XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method

S - Sealed

* Default handle color is white

Direction of Cable Strain Relief

0 - Straight cable strain relief

Dust Cap

A - No dust cap supplied

B - Dust cap rubber lanyard

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

F - Dust cap PA lanyard (125mm)

Modification Code for mode 3 combination (4 Letters)

ECCV - Connection cable IEC type 2 connector on 2-end

GBCV - Connection cable GBCV connector on 2-end

EJCV - Connection cable IEC type 1 connector on 2-end
(same connector as J2CE)

J2CE - Connection cable SAE-J1772 connector 2-end
(same connector as EJCV)

Direction of Cable Strain Relief

0 - Straight cable strain relief

Dust Cap

A - No dust cap supplied

B - Dust cap rubber lanyard

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

F - Dust cap PA lanyard (125mm)

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification


179 - Handles in black color

Dimensions shown in mm

Specifications and dimensions subject to change

www.ittcannon.com

GBCV Connector



How to order

GBCV	16	2	1	-017	S	0	A	-001
------	----	---	---	------	---	---	---	------

Connector Series & Style	
Current Rating (Cable size)	
Cable Rating	
Powering System (Connector Voltage Rating)	
Cable Length (3 Digits)	
Sealing Method	
Direction of Cable Strain Relief	
Dust Cap	
Modification Code - If Applicable (3 digits)	

Explanation

- Connector Series & style***
GBCV - EVC GB/T 20234 Connector vehicle coupler
- Current Rating (Cable size)**
10 - 10A (1 phase only)
16 - 16A
32 - 32A
- Cable Rating**
2 - Level 2

- Powering System (Connector Voltage Rating)**
1 - Single phase (250VAC)
3 - Three phase (440VAC)
- Cable Length (3 Digits)**
XXX - Length in 0.1m*XXX (017 = 1.7m)
- Sealing Method**
S - Sealed
- Direction of Cable Strain Relief**
0 - Straight cable strain relief



- Dust Cap**
A - No dust cap supplied
B - Dust cap rubber lanyard
C - Dust cap stainless steel lanyard (155mm)
D - Dust cap stainless steel lanyard (125mm)
E - Dust cap PA lanyard (155mm)
F - Dust cap PA lanyard (125mm)
- Modification Code - If Applicable (3 digits)**
001 to 999 - For customer specific modification
179 - Handles in black color

* Default handle color is white



Dimensions shown in mm
Specifications and dimensions subject to change

GBIV Inlet



How to order

GBIV 16 2 1 -017 S 0 A 1 A 0 A 0 -001

Connector Series & Style

Current Rating (Cable size)

Cable Rating

Powering System (Connector Voltage Rating)

Cable Length (3 Digits)

Sealing Method

Compression Limiter / Metal Inserts in Flange Holes

Dust Cap / Spring Cap

Drain Spout

Locking Device

Rubber Boot

Mounting Hole Pattern

Flange Gasket

Modification Code - If Applicable (3 digits)

Explanation

Connector Series & style

GBIV - EVC GB/T 20234 Connector vehicle inlet

Current Rating (Cable size)

10 - 10A (1 phase only)

16 - 16A

32 - 32A

Cable Rating

2 - Level 2

Powering System (Connector Voltage Rating)

1 - Single phase (250VAC)

3 - Three phase (440VAC)

Cable Length (3 Digits)

XXX - Length in 0.1m*XXX (017 = 1.7m)

Sealing Method

S - Sealed

Compression Limiter / Metal Inserts in Flange Holes

0 - Without compression limiter/inserts

1 - Compression limiter (front mounting)

3 - Compression limiter with threaded inserts
M5 (front mounting)

Dust Cap / Spring Cap

A - No dust cap supplied

C - Dust cap stainless steel lanyard (155mm)

D - Dust cap stainless steel lanyard (125mm)

E - Dust cap PA lanyard (155mm)

F - Dust cap without lanyard for OD

M - Dust Cap PA Lanyard, ring terminal (125mm)

N - Dust cap PA lanyard (125mm)

Drain Spout

0 - Without drain spout

1 - With drain spout without tube

2 - With drain spout with tube; 1m long

3 - With drain spout with tube, 2m long

Locking Device

A - No locking device

B - Motorized switch assembly (No male connector
supplied for locking device)

C - Motorized switch assembly including connector
& 300mm cable

D - Motorized switch assembly including connector
& 300mm cable & socket contacts on single wires

Rubber Boot

0 - No rubber boot supplied

Mounting Hole Pattern

A - Standard pattern

Flange Gasket

0 - No flange gasket supplied

1 - With flange gasket

Modification Code - If Applicable (3 digits)

001 to 999 - For customer specific modification

Dimensions shown in mm


Specifications and dimensions subject to change

www.ittcannon.com




EV wiring plans


ECIER/ECIV/GBIE/GBIV




ECCE/ECCV




J2IV/EJIV



GBCE



GBCV/J2CE/EJCV



Current Ratings GBCV	R4	Rc
10A	1.8KΩ/0.5W	1.5KΩ/0.5W
16A	2.7KΩ/0.5W	680Ω/0.5W
32A	3.3KΩ/0.5W	220Ω/0.5W
63A	3.3KΩ/0.5W	100Ω/0.5W

Current Ratings J2CE/EJCV	R4 (R7)	Rc (R6)
All ratings	330Ω/1W	150Ω/3W

Additional ITT Cannon products for e-mobility applications



APD SERIES

This full-plastic, proven bayonet series with IP69K sealing and color and mechanical coding is an ideal solution for harsh environments that require high sealing grades.



TRIDENT SERIES

This versatile range of metal and plastic electrical connectors with fully interchangeable contacts is available in rectangular and circular configurations, supporting the widest variety of harsh-environment applications.



CCS1 & CCS2 COOLED HIGH POWER CHARGING SOLUTIONS

This innovative liquid cooled solution can deliver a charge of 500 A at 1,000 V and consists of connector, cable and optional cooling unit. The weight optimized cable design and minimized cable diameter delivers a highly flexible, ergonomic and easy-to-use solution.



CCS1 & CCS2 UNCOOLED CHARGING SOLUTIONS

This uncooled DC charging connector and cable solution is versatile, simple to install and service in-field and engineered to be easily customizable to meet specific customer applications and needs.

Connect with your ITT Cannon representative today
or visit us at www.ittcannon.com

Connect with the experts

ITT Cannon is a world leader in the design and manufacture of highly engineered solutions for global e-mobility markets.



Why ITT

ITT is a focused multi-industrial company that designs and manufactures highly engineered critical components and customized technology solutions. ITT's Cannon brand is a leading global manufacturer of connector products serving international customers in aerospace, defense, medical, industrial and transportation end markets. ITT's Connector business, which also includes the Veam and BIW Connector Systems brand, manufactures and supplies a variety of connectors and interconnects that make it possible to transfer data, signal and power in an increasingly connected world.

Connect with your ITT Cannon representative today or visit us at www.ittcannon.com

Follow us 

CHINA - Shenzhen City +86.755.2726.7888	GERMANY - Weinstadt +49.7151.699.0	ITALY - Lainate +39.02938721	KOREA +82.2.702.7111	SHANGHAI + 86.21.2231.2222.2	UK - Basingstoke +44.1256.347400
FRANCE +33.1.60.04.93.93	HONG KONG +852.2732.2720	JAPAN - Kanagawa +81.462.57.2010	MEXICO - Nogales +52.631.311005	SINGAPORE +65 66974205	USA - Irvine, CA +1.800.854.3028