












< List of part numbers with package codes > LQH2MCN220K02L $\,$, LQH2MCN220K02B

Shape



Notes

When applied Rated current to the Products, Inductance will be within $\pm 10\%$ of initial Inductance value.

When applied Rated current to the Products, temperature rise caused by self-generated heat shall be limited to $40\,^{\circ}$ max.

References

Packaging code	Specifications	Minimum quantity
L	$_{\Psi}$ 180mm Embossed taping	3000
В	Packing in bulk	100

Mass (Typ.)	
1 piece	0.010g

Specifications

Inductance	22μH ±10%
Inductance test frequency	1MHz
Rated current (Itemp) (Based on Temperature rise)	185mA
Max. of DC resistance	2.73Ω
Avg. of DC resistance	2.1Ω±30%
Self resonance frequency (min.)	30MHz
Operating temperature range (Self-temperature rise is not included)	-40~85℃
Class of magnetic shield	No Shield

1 of 2



1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Inductance-Frequency characteristics (Typ.)



Temperature rise characteristics (Typ.)



Inductance-Current characteristics (Typ.)



2 of 2

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.