Note: This datasheet may be out of date.

Please download the latest datasheet of LQM21FN470N00# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQM21FN470N00%23

"#" indicates a package specification code.

## LQM21FN470N00#

### Bias Current Characteristics Improved

















< List of part numbers with package codes >

LQM21FN470N00L


LQM21FN470N00K

LQM21FN470N00B



## Appearance & Shape





| Dimension of t | Inductance: 1.0 to 2.2µH | 0.85±0.2 |
|----------------|--------------------------|----------|
|                | Inductance: 4.7 to 47µH  | 1.25±0.2 |



## References

| Packaging | Specifications   | Standard<br>Packing<br>Quantity |
|-----------|------------------|---------------------------------|
| L         | 180Embossed Tape | 3000                            |
| K         | 330Embossed Tape | 10000                           |
| В         | Bulk(Bag)        | 1000                            |

| Mass (typ.) |        |
|-------------|--------|
| 1 piece     | 0.016g |

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



LQM21FN470N00#

CS

Note: This datasheet may be out of date.

Please download the latest datasheet of LQM21FN470N00# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=LQM21FN470N00%23

"#" indicates a package specification code.



# **Specifications**

| L size   | 2.0±0.2mm     |
|--|---------------|
| 2 3.23   |               |
| W size   | 1.25±0.2mm    |
| T size   | 1.25±0.2mm    |
| Size code inch (mm)  | 0805 (2012)   |
| Inductance   | 47μH±30%      |
| Inductance Test Frequency  | 1MHz          |
| Rated current (Itemp) (Based on Temperature rise)                  | 7mA           |
| Max. of DC resistance  | 0.78Ω         |
| Class of magnetic shield   | Ferrite Core  |
| Self resonance frequency (min.)                                    | 7.5MHz        |
| Operating Temperature Range(Self-temperature rise is not included) | -40°C to 85°C |
| DC Resistance Intermediate Values                                  | 0.60Ω±30%     |
| Series   | LQM21FN_00    |

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



# LQM21FN470N00#

Note: This datasheet may be out of date.


Please download the latest datasheet of LQM21FN470N00# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=LQM21FN470N00%23

"#" indicates a package specification code.



## Characteristic Data





Impedance - Current Characteristics

Impedance - Frequency Characteristics

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

