


WJ15EDGVC-3.5/3.81

PLUG-IN TERMINAL BLOCK



PCB connector

Rated current: 8 A

Rated voltage: 300 V

Pitch: 3.5 mm/3.81 mm

Mounting: Wave soldering



For reference only!version1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	-	300
Rated Current [A]	8	-	8
Wire Range [AWG]	/		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	160	160	250
Rated Current [A]	7	7	7
Impulse withstand voltage [KV]	2.5	2.5	2.5
Conductor cross section[solid/flexible] [mm ²]	/		

Material

Insulation Material	PA66
---------------------	------


Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data

Pitch/Poles [mm]/[P]	3.5 , 3.81/2-24
Stripping Length [mm]	/
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105
Soldering temperature	260°C/5S
Pin dimensions [mm]	0.8*0.8
PCB Hole Diameter [mm]	Ø1.4

Dimensions

PCB opening diagram



Accessories

WJ15EDGVC-3.5/3.81

PLUG-IN TERMINAL BLOCK



[WJ15EDGKN-3.5/3.81](#)



[WJ15EDGK-3.5/3.81](#)



[WJ15EDGKA-3.5/3.81](#)



[WJ15EDGKB-3.5/3.81](#)




[WJ15EDGKC-3.81](#)



[WJ15EDGKD-3.5/3.81](#)



[WJ15EDGA-3.5/3.81](#)



[WJ15EDGB-3.5/3.81](#)